

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Item	Size (inches)	Cavity Size (inches)	# of Cavities
<u>39206</u>	10-1/2" x 8-3/4" x 1-1/2"	2" x 1-7/8" x 1"	12
<u>39201</u>	14-1/2" x 10-1/8" x 1-7/8"	3-1/2" x 2-3/4" x 1-1/4"	9
<u>39202</u>	14-3/8" x 10-1/8" x 1-3/4"	3" x 3" x 1-1/4"	12
<u>39209</u>	9-7/8" x 7-9/16" x 1"	3" x 1-1/2" x 1"	10
<u>39203</u>	Lid for Kitting Tray 39206		
<u>39204</u>	Lid for Kitting Tray 39201		
<u>39205</u>	Lid for Kitting Tray 39202		
<u>39212</u>	Lid for Kitting Tray 39209		

FEATURES:

- · Used for kitting and to help organize the workstation
- Durable conductive styrene
- Die-cut drop-in covers available separately
- · Reusable, ensuring best value
- · Great container for Kanban
- · Made in the United States of America

SPECIFICATIONS:

Property	Typical Value	ASTM
Specific Gravity	1.09	D-792
Tensile Strength	4,200 psi	D-638
Tensile Elongation	40%	D-638
Flexural Modulus	220,000 psi	D-790
Flexural Strength	6,700 psi	D-790
Total/Free Sulfur	<0.15% / <0.004%	
Chlorides	<0.3 PPM	
Outgassing &		
Corrosivity	Low	
5KV Decay Time	<0.01 sec @ 10% RH	
Surface Resistance	1 x 10 ³ to < 1 x 10 ⁸ ohms per ANSI/ESD STM11.13	

Note: Per Packaging standard ANSI/ESD S541 section 6.1 Inside an EPA "Packaging uesd within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be: 1. Low charge generation, 2. Dissipative or conductive materials for intimate contact."

Tolerances are ± 1/16"

Specifications and procedures are subject to change without notice.



United States of America

DATE:

July

2016

CONDUCTIVE KITTING TRAYS



PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com

DRAWING NUMBER 39201