

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Pocket Fold-up Thermometer

4.5" stainless steel probe adjusts from 0 to 180° With detents at 45°, 90°, 135° and 180°

Features:

- Wide °C/°F switchable temperature range -58 to 572°F (-50 to 300°C)
- Fold up probe 4.5" (114mm) adjusts from 0° to 180° for best measurement and viewing angle
- Large LCD display with 0.1 degree resolution
- Auto power off after 1 hour or when probe is placed in stored position
- Data Hold and Min/Max recordings
- Fast response time one second under normal conditions
- · Complete with wrist strap and one AAA battery



Specifications	
Range	-58 to 572°F (-50 to 300°C)
Accuracy	±1.8°F (-22 to 482°F); ±1°C (-30 to 250°C)
Resolution	0.1°/1° resolution
Dimensions	6.1 x 2.0 x 0.8" (154 x 50 x 20mm)
Weight	2.5oz (71g)

Ordering Information:

39272	Pocket Fold-up Thermometer
409992	Vinvl Pouch Carrying Case

