



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




REV	DOCUMENT	CHANGED BY	CHECK
14	0038331	DSK 03APR09	CMH

14	0038551	DSR	05APR09	CM
----	---------	-----	---------	----

.375 MAX FREE POSITION
 .203 MIN OPERATING POSITION
 .125 MAX DEPRESSED POSITION
 1.88
 1.33
 .6
 .11
 POSITIVE OVERTRAVEL STOP IS PROVIDED ON ROD UNDER SPRING
 Ø.250
 Ø.187
 Ø.250 MAX
 3X 4-40 UNC X (.125) ROUND HEAD TERMINAL SCREW AND LOCKWASHER
 V3-13 BASIC SWITCH
 FLEXIBLE INSULATOR
 2X 6-32 UNC THREAD
 .31
 (1.592)

NOTES

- 1 - NOTCH IN ACTUATOR ROD WILL PERMIT .035 DISPLACEMENT BETWEEN END OF ROD AND HOLE IN BRACKET
- 2 - PLASTIC PARTS ARE MADE OF MINERAL FILLED PHENOLICS
- 3 - WITH ROD IN EITHER ACTUATED POSITION, BASIC SWITCH PLUNGER MUST HAVE .010 MIN OVERTRAVEL AND WITH ROD IN FREE POSITION BASIC SWITCH PLUNGER MUST HAVE .005 MIN RELEASE TRAVEL

CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: INCH TOLERANCES UNLESS NOTED:			DRAWN	KDR	09SEP96	Honeywell									
TOTAL TRAVEL .250 APPROX PUSH DIRECTION .187 APPROX PUSH DIRECTION FULLY DEPRESSED FORCE ---- 4 LB MAX		CONTACT ARRANGEMENT S P D T		NO PLACES X ± - ONE PLACE .X ± 0.030 TWO PLACE .XX ± 0.015 THREE PLACE .XXX ± 0.005 ANGLES X ± -			CHECK	-	-								TITLE ASSEMBLY - SWITCH		
		15.1A 1/2HP 125 OR 250 VAC 1/2A 125 VDC, 1/4A 250 VDC 5A 125 VAC "L"					THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.			INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY			SIZE	TYPE	CAGE CODE	DRAWING NAME			
															B	I	-	3AC6	
						THIRD ANGLE PROJECTION 			Pro/ENGINEER 3D			SCALE	2 : 1	WEIGHT- .092 LB		SHEET 1 OF 1			