

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# Scotch® Foil Tape 3326-A, 2.5 in

3M ID 70071352416, UPC 00051131854949

Overview Specifications Details



- Soft aluminum applies easily
- Can be used under all weather conditions
- Resists water vapor, odor and smoke transmission
- adhesive is protected until the liner is removed

## **Specifications**

#### Attribute Name Value

Color Silver

Width 2.5 Inch

### **Details**

- Soft aluminum applies easily
- Can be used under all weather conditions
- Resists water vapor, odor and smoke transmission
- adhesive is protected until the liner is removed
- For UL 181A and ULB-FX compliant
- Printed backing provides code compliance verification for building inspectors

3326 Foil Tape is recommended for use on UL listed rigid fiberglass air duct in accordance with the Duct Board Manufacturers installation instructions.

Scotch® Foil Tape 3326 is especially designed for use on UL listed flexible and rigid air ducts. Its specially formulated acrylic adhesive bonds quickly and holds even at -25oF. Its soft aluminum handles and applies easily but still provides strength for UL 181A and ULB-FX compliance. The printed backing provides code compliance verification for building inspectors.