

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Sound Level Meter with Backlit Display



Features:

- High accuracy meets ANSI and IEC 651 Type 2 standards
- High and Low measuring ranges
- · Data Hold and Max Hold functions
- · Backlit display to view in dimly lit area
- · Complete with microphone wind screen and 9V battery

Applications:

- · Enforcing community noise ordinances
- · Meeting government safety issues (OSHA)
- · Installing audio systems
- Product noise certification and reduction



Specifications		
Display Counts	2000 count LCD	
Range	Low: 35 to 100dB	
	High: 65 to 130dB	
Basic Accuracy	±1.5dB	
Weighting (A & C)	Yes	
Response Time (Fast/Slow)	Yes	
Condenser Microphone	0.5" (12.7mm)	
Dimensions	8.2x2.1x1.25"(210x55x32mm)	
Weight	8.1oz (230g)	

Ordering Information:

407732...........Sound Level Meter with Backlit Display 407732-NISTSound Level Meter with Backlit Display with NIST

