



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SRSL 4-T15



tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type Cat.-No. Qty.p.pck.
SRSL 4-T15 41064.2 green/yellow 100

Ratings:

Dimensions TS 15
LxBxH (mm) 32x7x32
Stripped Length 9 mm

Max Rated Cross Section

Single Wire (solid) 0.2-4 mm²
Stranded Wire (flexible) 0.2-4 mm²
Wire Size AWG 22-10

SRSLN 2.5-T32



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.
SRSLN 2.5-T32 41057.2 green/yellow 100

Ratings:

Dimensions TS 32
LxBxH (mm) 44x6x43
Stripped Length 10 mm

Max Rated Cross Section

Single Wire (solid) 0.2-4 mm²
Stranded Wire (flexible) 0.2-2.5 mm²
Wire Size AWG 22-14

EARTH TERMINAL BLOCKS

SRSLN 2.5-T35



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.
SRSLN 2.5-T35 41058.2 green/yellow 100


Ratings:

Dimensions TS 35
LxBxH (mm) 52x6x39
Stripped Length 10 mm

Max Rated Cross Section

Single Wire (solid) 0.2-4 mm²
Stranded Wire (flexible) 0.2-2.5 mm²
Wire Size AWG 22-14

SRSL 2.5-T32



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.
SRSL 2.5-T32 41055.2 green/yellow 100

Ratings:

Dimensions TS 32
LxBxH (mm) 42x6x52
Stripped Length 10 mm

Max Rated Cross Section

Single Wire (solid) 0.2-4 mm²
Stranded Wire (flexible) 0.2-2.5 mm²
Wire Size AWG 22-14