



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Double Coated Paper Tapes

401M • 410M

Technical Data

November, 2009

Product Description 3M™ Double Coated Paper Tapes 401M and 410M utilize a natural rubber adhesive system that offers good to excellent adhesion to many types of surfaces.

Environmental Advantage These products use a solvent free manufacturing process.

Construction	Products	3M™ Double Coated Paper Tape	
		401M	410M
Adhesive Family:		860	860
Adhesive Type:		Natural Rubber	Natural Rubber
Adhesive Carrier:		Treated Paper	Treated Paper
Tape Color:		Off-white	Off-white
Liner Color:		Green Plaid Paper	Green Plaid Paper
Approximate Thickness:			
Tape Thickness <i>(without the liner)</i>		0.009 in. (0.23 mm)	0.006 in. (0.15 mm)
Liner Thickness		0.003 in. (0.075 mm)	0.003 in. (0.075 mm)

3M™ Adhesive 860 is a soft rubber-resin pressure-sensitive adhesive system and features high initial adhesion and good holding power to a wide variety of materials.

Typical Physical Properties and Performance Characteristics **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

Products	3M Double Coated Paper Tape	
	401M	410M
Adhesion to Steel: ASTM D 3330 modified 90° peel, 72 hr. RT dwell	65 oz./in. (71 N/100 mm)	50 oz./in. (56 N/100 mm)
Relative High Temperature Operating Ranges:		
Long Term (days, weeks)	150°F (65°C)	150°F (65°C)
Short Term (minutes, hours)	180°F (82°C)	200°F (93°C)
Relative Solvent Resistance:	Medium	Medium
U.V. Resistance:	Good	Good

3M™ Double Coated Paper Tapes

401M • 410M

Application Techniques Bond strength is dependent upon the amount of adhesive-to-surface contact. Firm application pressure helps ensure better adhesive contact and improve bond strength.

To obtain optimum adhesion, the bonding surfaces must be clean, dry, and uniform. Some typical surface cleaning solvents are isopropyl alcohol or heptane.*

Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

***Note:** When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

-
- Application Ideas**
- Splicing and core starting of papers, foils, films, fabrics etc.
 - Mounting rubber or photopolymer printing plates to print cylinders.
 - Attaching of golf club grips.
 - Temporary holding while parts are being finished in the milling process.

Application Equipment For additional dispenser information, contact your local 3M sales representative, or the toll free 3M sales assistance number at 1-800-362-3550.

Available Sizes Please contact your 3M sales representative or contact 3M customer service at 1-800-362-3550 for details on available sizes.

Storage Store in original cartons at 70°F (21°C) and 50% relative humidity.

Shelf Life If stored under proper conditions, product retains its performance and properties for one year from date of manufacture.

3M™ Double Coated Paper Tapes

401M • 410M

Certification/ Recognition

MSDS: 3M has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

TSCA: These products are defined as articles under the Toxic Substances Control Act and therefore, are exempt from inventory listing requirements.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Adhesives and Tapes Division Converter Markets

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-223-7427 • 651-778-4244 (fax)
www.3M.com/converter



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2009 70-0709-3796-9 (11/09)