



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Tightening torque/thread 2.0 Nm/M 4 Inspection Test Pattern Size A 5


Type Cat. No. Qty.p.pck.
SRSL 10-T35 41213.2 green/yellow 80

Ratings:

Dimensions TS 35
 LxBxH (mm) 56x10x47
 Stripped Length 12 mm

Max Rated Cross Section

Single Wire (solid) 0.2-10 mm²
 Stranded Wire (flexible) 0.2-10 mm²
 Wire Size AWG 20-8



Tightening torque/thread 4.0 Nm/M 5 Inspection Test Pattern Size B 7


Type Cat. No. Qty.p.pck.
SRSL 16-T32 41196.2 green/yellow 50

Ratings:

Dimensions TS 32
 LxBxH (mm) 50x12x63
 Stripped Length 12 mm

Max Rated Cross Section

Single Wire (solid) 2.5-25 mm²
 Stranded Wire (flexible) 2.5-16 mm²
 Wire Size AWG 12-6



Tightening torque/thread 5.0 Nm/M 6 Inspection Test Pattern Size B 8

Type Cat. No. Qty.p.pck.
SRSL 35-T32 41198.2 green/yellow 20

Ratings:

Dimensions TS 32
 LxBxH (mm) 58x16x76
 Stripped Length 20 mm

Max Rated Cross Section

Single Wire (solid) 2.5-50 mm²
 Stranded Wire (flexible) 2.5-35 mm²
 Wire Size AWG 12-2



Tightening torque/thread 4.0 Nm/M 5 Inspection Test Pattern Size B 7

Type Cat. No. Qty.p.pck.
SRSL 16-T35 41197.2 green/yellow 50

Ratings:

Dimensions TS 35
 LxBxH (mm) 56x12x58
 Stripped Length 12 mm

Max Rated Cross Section

Single Wire (solid) 2.5-25 mm²
 Stranded Wire (flexible) 2.5-16 mm²
 Wire Size AWG 12-6