



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type Cat.-No. Qty.p.pck.
SRD 4-800 41025.2 beige 80


Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	611 750 V	947-7-1 800 V
Rated Current	30 A AWG 12	34 A	34 A	32 A

Max Rated Cross Section

Single Wire (solid)	0.2-4 mm ²
Stranded Wire (flexible)	0.2-4 mm ²
Wire Size	AWG 22-12

Dimensions	TS 32	TS 35
LxBxH (mm)	61x7.5x65	61x7.5x60
Stripped Length	9 mm	



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.
SR 2.5 41296.2 beige 100
SR 2.5 41296.5 blue 100

Additional colors available. See page 114.

Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	611 750 V	947-7-1 800 V
Rated Current	20 A AWG 14	26 A	26 A	24 A

Max Rated Cross Section

Single Wire (solid)	0.2-4 mm ²
Stranded Wire (flexible)	0.2-2.5 mm ²
Wire Size	AWG 22-14

Dimensions	TS 32	TS 35
LxBxH (mm)	48x5x52	48x5x47
Stripped Length	7 mm	

Type:	Cat.-No.	Qty.p.pck.	Terminal accessories	Type:	Cat.-No.	Qty.p.pck.
AP 4/800 V	2159.2 beige	20	End plate	AP 2.5-10	2001.2 beige 2001.5 blue	50
			Isolation partition	TW 2.5-10	2002.2 beige 2002.5 blue	50
			Separator	TRS 3	2566.2 beige	100
ES 32/35 Combi	1424.2 beige	50	End bracket	ES 32/35 Combi	1424.2 beige	50
ES 32/K/ST	2827.0			ES 32/K/ST	2827.0	
ES 35/2/K	2826.2 beige			ES 35/2/K	2826.2 beige	
ES 35/K/ST	2828.0	50	End bracket	ES 35/K/ST	2828.0	50
STB 8.5/2.3	2075.0			Test socket	STB 8.5/2.3	
PS 2.3	2007.0	20	Test plug	PS 2.3	2007.0	20
			Switchable link			
			Connection sleeve			
			Screw			
			Warning tag (German)	AD 4	2712.0	50
			Warning tag (English)	AD 4 E	2713.0	50
			Plastic screw for warning tag	BSK M 2.5x22	2080.0	100
			Cross-connection	Q2	2567.0	50
			Cross-connection	Q3	2568.0	50
			Cross-connection	Q4	2569.0	20
			Cross-connection	Q10	2570.0	10