

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







3M™ Electrically Conductive Connector Covers 4270 Series

Conductive Composite

Connector Covers 4270 Series are permanently volume conductive and free of carbon black particulate. The Connector Covers 4270 Series do not leave black marks and are more suited to clean situations. Meets the requirements of NASM5501 31/32.

Noncorrosive

Connector Covers 4270 Series are noncorrosive and produce no visible corrosion when tested to Federal Test Method 101C using Kovar test plates.

Conformability

The material used in the covers were also selected for its resilience. Properly sized, the covers provide a snug, secure fit. This helps keep connectors clean and prevents the cover from accidentally falling off.



Material Properties	Test Method	Typical Value
Resistivity	ASTM D991	<10 ⁵ ohm-cm
Contact Corrosivity	FTM 101C Metod 3005 (Kovar plate)	Pass
Crayoning	3M	Not visible
Elongation	ASTM D638	24%
Tensile	ASTM D638	2700 psi
Vicat Softening	ASTM MD 1525	85° C
Outgassing	ASTM E595	Pass
Chemical Susceptibility*	Reactions	
Dilute Acids	Slight Attack	
Dilute Alkalines	Slight Attack	
Concentrated Acids	Slight Attack	
Concentrated Alkalines	Slight Attack	
Methanol, Ethanol, and Isopropanol	Resistant	
Hydrocarbons	Slight Attack	
Ketones	Slight Attack	
Oil and Gasoline	Slight Attack	

^{*}ASTM F925




Product Data Sheet

3M[™] Circular Connector Covers 4270 Series

Product Description	Old Prod. Desc.	"A"	"B"	"C"	"D"		
Packaged 100/bag; 10 bags/box							
4270 M5501-31A-250	4270-4R	.670	.500	.250	.336		
4270 M5501/31A-313	4270-5R	.670	.500	.313	.399		
4270 M5501/31A-375	4270-6R	.670	.500	.375	.461		
4270 M5501/31A-413	4270-8Y	.670	.625	.413	.483		
4270 M5501/31A-480	4270-8R	.740	.500	.480	.540		
4270 M5501/31A-500	4270-9R	.750	.500	.500	.586		
4270 M5501/31A-530	4270-10Y	.750	.625	.530	.595		
4270 M5501/31A-605	4270-10R	.840	.500	.605	.665		
4270 M5501/31A-655	4270-12Y	.860	.625	.655	.715		
4270 M5501/31A-720	4270-12R	.970	.500	.720	.755		
4270 M5501/31A-785	4270-14Y	1.031	.625	.785	.845		
4270 M5501/31A-850	4270-14R	1.125	.500	.850	.905		
4270 M5501/31A-893	4270-16Y	1.125	.625	.893	.963		
4270 M5501/31A-973	4270-16R	1.220	.500	.973	1.035		
4270 M5501/31A-1028	4270-18Y	1.250	.625	1.28	1.088		
4270 M5501/31A-1093	4270-18R	1.330	.562	1.093	1.155		
4270 M5501/31A-1125	4270-19R	1.400	.562	1.125	1.213		

3M	3M Logo
	ANSI-ESD S8.1 Symbol
M5501/31A	Model Number





Product Description	Old Prod. Desc.	"A"	"B"	"C"	"D"			
Packaged 50/bag; 10 bags/box								
4270 M5501/31A-1150	4270-20Y	1.406	.625	1.150	1.215			
4270 M5501/31A-1231	4270-20R	1.465	.562	1.231	1.301			
4270 M5501/31A-1270	4270-22Y	1.500	.625	1.270	1.340			
4270 M5501/31A-1340	4270-22R	1.590	.562	1.340	1.410			
4270 M5501/31A-1390	4270-24Y	1.640	.625	1.390	1.460			
4270 M5501/31A-1463	4270-24R	1.700	.562	1.463	1.533			
4270 M5501/31A-1540	4270-25Y	1.810	.625	1.540	1.580			
4270 M5501/31A-1645	4270-28Y	1.875	.625	1.645	1.718			
4270 M5501/31A-1715	4270-28R	1.950	.562	1.715	1.790			
Packaged 25/bag; 10 bags/box								
4270 M5501/31A-1890	4270-32Y	2.125	.625	1.890	1.970			
4270 M5501/31A-1965	4270-32R	2.220	.562	1.965	2.040			
4270 M5501/31A-2140	4270-36Y	2.340	.625	2.140	2.210			
4270 M5501/31A-2215	4270-36R	2.435	.600	2.215	2.290			
4270 M5501/31A-2960	4270-48R	3.225	.600	2.960	3.050			



Product Data Sheet

3M[™] Connector Covers, Type "D", 4270 Series





Product Description	Old Prod. Desc.	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"
Nominal Dimensions Packaged 100/bag; 10 bags/box									
4272 M5501/32A-50P	4272-50P	2.112	2.179	2.279	.636	.536	.469	.280	.240
4272 M5501/32A-50S	4272-50S	2.049	2.116	2.216	.574	.474	.407	.280	.240
4272 M5501/32A-37P	4272-37P	2.216	2.283	2.383	.530	.430	.363	.280	.240
4272 M5501/32A-37S	4272-37S	2.143	2.210	2.310	.462	.362	.295	.280	.240
4272 M5501/32A-25P	4272-25P	1.586	1.635	1.735	.530	.430	.363	.280	.240
4272 M5501/32A-25S	4272-25S	1.495	1.562	1.662	.462	.362	.295	.280	.240
4272 M5501/32A-15P	4272-15P	1.040	1.107	1.177	.512	.436	.369	.280	.240
4272 M5501/32A-15S	4272-15S	.955	1.022	1.122	.462	.362	.295	.280	.240
4272 M5501/32A-9P	4272-9P	.708	.775	.849	.512	.434	.367	.280	.240
4272 M5501/32A-9S	4272-9S	.627	.694	.794	.462	.362	.295	.280	.240

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



Electronics Materials Solutions Division Static Control Products

926 JR Industrial Drive Sanford, NC 27332-9733 Toll-Free: 866-722-3736 International: 919-718-0000 Email: 3mstaticinfo@mmm.com www.3Mstatic.com