

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## wakefield-vette

Standard P/N	Width in. (mm)	lominal Dimensions Length "A" in. (mm)	Height in. (mm)	Semiconductor Mounting Hole Pattern		ance at Typical Load Forced Convection	Weight lbs. (grams)
431 K 433 K	4.750 (120.7) 4.750 (120.7)		3.000 (76.2) 3.000 (76.2)	None None	55°C @ 50W 42°C @ 50W	0.40°C/W @ 250 LFM 0.28°C/W @ 250 LFM	0.7800 (353.81) 1.4900 (675.86)
0.055 (1.4) 4.750 (120.7) 0.375 (9.6)	3.000 (76.2)	1.335 (33.9)	A"	0.095 R SERIES (2.4) 4.375 (111.1) 0.500 (12.7)	"A" "B" 2.000 (76.2) 2.000 (5 5.500 (139.7) 4.500 (1 9.87 (1.00)) 5.500 (139.7) 4.500 (1 9.87 (1.00)) 5.500 (139.7) 4.500 (1 9.87 (1.00)) 5.500 (139.7) 4.500 (1 9.87 (1.00)) 5.500 (139.7) 4.500 (1 9.87 (1.00)) 5.500 (1 9.90) 5.500 (1 9.87 (1.00)) 5.500 (1 9.90) 5.500 (1 9.90) 5.500 (1	14.3) CONVECTION CHA  AIR VELOCITY (LFN 0 100 200 300 400 500 600 700	RACTERISTICS

0 50 100 150 200 250 300 350 400 450 500 POWER DISSIPATION (WATTS)

