



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Microprocessor Calibrator Thermometer

Source and Measure 8 thermocouple type devices
 One model for multiple thermocouple types (J, K, T, E, C, R, S and N) with precision output displayed as mV or °C/°F

Features:

- High accuracy calibration function simulates precision thermocouple outputs for use in calibrating thermometers, transmitters, controllers or recorders
- Basic accuracy of $\pm 0.15\%$ of reading over wide ranges
- $0.1^\circ/1^\circ$ resolution for J, K, T and E Types; 1° for C, R, S and N Types
- Five stored calibration values for fast calibrations
- Displays output in terms of millivolts or temperature based on thermocouple tables
- 4 digit LCD display is easy to read with thermocouple type indication
- Unique handheld Oyster case design features large digital display built into "flip-up" cover automatically shuts off when closed
- Portable and rugged industrial design for field, plant or benchtop use
- Operates on alkaline batteries, rechargeable batteries or AC adaptor
- Standard Thermometer Calibration cables (terminated with subminiature connectors on either side) comes standard with the meter. Optional Process Calibration Cable is terminated with spade lug for process applications



Specifications	Ranges for Calibrate and Measure modes		Accuracy
Type J	-58 to 1830°F	(-50 to 1000°C)	0.15% rdg $\pm 1^\circ$
Type K	-58 to 2498°F	(-50 to 1370°C)	0.15% rdg $\pm 1^\circ$
Type T	-184 to 752°F	(-120 to 400°C)	0.15% rdg $\pm 1^\circ$
Type E	-58 to 1382°F	(-50 to 750°C)	0.15% rdg $\pm 1^\circ$
Type C	32 to 3272°F	(0 to 1800°C)	0.15% rdg $\pm 1^\circ$
Type R	32 to 3182°F	(0 to 1750°C)	0.15% rdg $\pm 1^\circ$
Type S	32 to 3182°F	(0 to 1750°C)	0.15% rdg $\pm 1^\circ$
Type N	-58 to 2372°F	(-50 to 1300°C)	0.15% rdg $\pm 1^\circ$
Voltage	-5.00mV to +55.00mV	10 μ V	10 μ V ± 1 d
Resolution	0.1° (up to 999.9) or 1° (over 999.9°)		
Cold Junction Compensation	0.03°C/°C (0.02°F/°F)		
Input Impedance	10 Mohm		
Sampling Time	4 times/second		
Dims/Weight	3.8 x 4.2 x 1.8" (96 x 108 x 45mm)/ 17oz		

Ordering Information:

433201Microprocessor Calibrator Thermometer (115V AC Adaptor)
 433201-NIST433201 with Calibration Traceable to NIST Certificate

