



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# FLIR

The FLIR ONE Pro gives you the power to find invisible problems faster than ever. Combining a higher-resolution thermal sensor able to measure temperatures up to 400 °C (752 °F) with powerful measurement tools and report generation capability, the FLIR ONE Pro will work as hard as you do. Its revolutionary VividIR™ image processing lets you see more details and provide your customers with proof that you solved their problem right the first time. The updated design includes the revolutionary OneFit™ adjustable connector to fit your phone, without taking the phone out of its compatible protective case. An improved FLIR ONE app lets you measure multiple temperatures or regions of interest at once and stream to your smartwatch for remote viewing. Whether you're inspecting electrical panels, looking for HVAC problems, or finding water damage, the new FLIR ONE Pro is a tool no serious professional should be without.

## VividIR IMAGE PROCESSING

*See It & Solve It - Sharpest Mobile Thermal Imaging Performance Lets You Detect Problems with Precision and Accuracy, then Document Your Fix for the Customer*

- Most advanced image resolution enhancement detects the thermal details you need to find problems fast
- With 160 x 120 thermal resolution, FLIR ONE Pro uses FLIR's highest resolution micro thermal camera and can measure temperatures as high as 400 °C (752 °F)
- FLIR MSX® embosses visible edges from the 1440 x 1080 HD camera onto thermal imagery to create a sharper, easier to understand picture

## OneFit CONNECTOR

*Leave Your Case On - Adjustable Connector Means You Don't Have to Choose Between Thermal Vision and Safeguarding Your Device when Using Compatible Protective Cases*

- Adjust length of USB-C and Lightning connector up to an additional 4 mm
- Reversible connectors for Android and iOS
- Secure the FLIR ONE to your mobile device while keeping your phone safe

## HARD-WORKING APP

*Work Like a Pro - Work-Based Features Include Advanced Capabilities for More Professional Problem Solving and Functionality*

- Use multiple real-time spot meters and regions of interest
- Access real-time thermal tips and tricks in the FLIR ONE app followed by professional reporting through FLIR Tools
- See around corners and in awkward spaces by connecting to your Apple Watch or Android smartwatch

## Specifications

General		FLIR One Pro	
Certifications	MFi (iOS version), RoHS, CE/FCC, CEC-BC, EN61233		
Operating temperature	0 °C – 35 °C (32 °F to 95 °F) , battery charging 0 °C to 30 °C (32 °F to 86 °F)		
Non-operating temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
Size	68mm W x34mm H x14mm D (2.7in x 1.3in x .6in)		
Weight	36.5g		
Mechanical shock	Drop from 1.8m (5.9ft)		
Video			
Thermal and visual cameras with MSX			
Thermal sensor	Pixel size 12µM, 8 – 14µM spectral range		
Thermal resolution	160x120		
Visual resolution	1440x1080		
HFOV / VFOV	55 ° ± 1 ° / 43 ° ± 1 °		
Frame rate	8.7Hz		
Focus	Fixed 15cm – Infinity		
Radiometry			
Scene dynamic range	-20 °C to 400 °C (-4 °F to 752 °F)		
Accuracy	±3 °C (5.4 °F) or ±5%, typical Percent of the difference between ambient and scene temperature. Applicable 60s after start-up when the unit is within 15 °C to 35 °C (59 °F to 95 °F) and the scene is within 5 °C to 120 °C (41 °F to 248 °F)		
Thermal sensitivity (MRTD)	150mK		
Emissivity settings	Matte: 95%, Semi-Matte: 80%, Semi-Glossy: 60%, Glossy: 30% Reflected background temperature is 22 °C (72 °F)		
Shutter	Automatic/Manual		
Power			
Battery life	Approximately 1h		
Battery charge time	40min		
Interfaces			
Video	Male Lightning (iOS), Male USB-C (Android)		
Charging	Female USB-C (5V/1A)		
App			
Video and still image display/capture	Saved as 1440x1080		
File formats	Photo – radiometric jpeg Video – MPEG-4 (file format MOV (iOS), MP4 (Android))		
Capture modes	Video, Photo, Time lapse		
Palettes	Gray (white hot), Hottest, Coldest, Iron, Rainbow, Contrast, Arctic, Lava and Wheel.		
Spot meter	Off / °C / °F. Resolution 0.1 °C / 0.1 °F		
Adjustable MSX distance	0.3m – Infinity		
Battery charge monitor	0 – 100%		

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
PH: +1 877.773.3547

**CHINA**  
FLIR Systems Co., Ltd  
Room 502, West Wing, Hanwei Building  
No. 7 Guanghua Ave.  
Chaoyang District, Beijing 100004, China  
Phone: +86 10-59797755

**SANTA BARBARA**  
FLIR Systems, Inc.  
6769 Hollister Ave.  
Goleta, CA 93117  
PH: +1 805.690.6600

**EUROPE**  
FLIR Systems, Inc.  
Luxemburgstraat 2  
2321 Meer  
Belgium  
PH: +32 (0) 3665 5100

www.flir.com  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 06/06/17

17-1746-OEM-FLIROne\_Pro