



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SHOP

### Ergonomic Symmetric Crimping Tool



### 436 16 Insulated Ergonomic Symmetric Crimping Tool

Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on red, blue, yellow insulated terminals on wires ranging from 0.75 - 6.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 16	mm	Inch	AWG	lbs.	Pkg.
	255	10.0	22 - 10 (0.75-6.0mm <sup>2</sup> )	1.2	1

50,000 Cycle Rated

SHOP

### Non-Insulated Crimping Tool



### 436 32 Non-Insulated Crimping Tool

For Non-insulated terminals, lugs, wire splices and solid/standard wires ranging from 0.75 - 6.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 32	mm	Inch	AWG	lbs.	Pkg.
			22 - 10 (0.75-6.0mm <sup>2</sup> )	1.2	1

50,000 Cycle Rated

SHOP

### Ergonomic Uninsulated Open Barrel Crimping Tool



### 436 22 Uninsulated Ergonomic Open Barrel Crimping Tool

Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on uninsulated open barrel connectors terminals on wires ranging from 0.5 - 6.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 22	mm	Inch	AWG	lbs.	Pkg.
	255	10.0	22 - 10 (0.5-6.0mm <sup>2</sup> )	1.2	1

50,000 Cycle Rated

SHOP

### Ergonomic End Splices/Ferrules Crimping Tool



### 436 11 Insulated & Uninsulated Ergonomic End Splices/Ferrules Crimping Tool

Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on wires ranging from 0.5 - 6.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 11	mm	Inch	AWG	lbs.	Pkg.
	212	8.35	22 - 10 (0.5-6.0mm <sup>2</sup> )	1.1	1

50,000 Cycle Rated

SHOP

### Ergonomic End Splices/Ferrules Crimping Tool



### 436 19 Insulated & Uninsulated Ergonomic End Splices/Ferrules Crimping Tool

Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on end splices/ferrules terminals on wires ranging from 4.0 - 10.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 19	mm	Inch	AWG	lbs.	Pkg.
	255	10.0	12 - 8 (4.0-10.0mm <sup>2</sup> )	1.2	1

50,000 Cycle Rated

SHOP

### Ergonomic End Splices/Ferrules Crimping Tool



### 436 20 Insulated & Uninsulated Ergonomic End Splices/Ferrules Crimping Tool

Precision ratchet crimp tool designed to provide consistent & reliable crimp connections on end splices/ferrules terminals on wires ranging from 10.0 - 25.0mm<sup>2</sup>. Ratchet action to ensure full crimp cycle with safety release. Factory set for precise crimping to guarantee performance.

#436 20	mm	Inch	AWG	lbs.	Pkg.
	255	10.0	6 - 4 (10.0-25.0mm <sup>2</sup> )	1.2	1

50,000 Cycle Rated

PREVIOUS

NEXT