



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



COVENTRY™ Clean Room Products

Division of Chemtronics

44070 Conical Foam Swabs

TDS # 44070

PRODUCT DESCRIPTION

The **44070 Conical Sealed Foam Swabs** are constructed from reticulated 100 pores per inch medical grade polyurethane foam which features the best open cell structure, providing excellent particle entrapment characteristics. The head is thermally bonded to the handle without using adhesives. The conical head tapers to a fine point for precision cleaning of hard to reach areas.

- Traps surface particles while cleaning
- Fiberless construction does not generate loose fibers or particles
- No adhesives or binders are used in the construction
- Good for tight tolerance work

AVAILABILITY

- | | |
|-----------------|---|
| 44070 | 3.2"(8.0 cm) Polypropylene Handle,
0.13" (3.3 mm), Conical Foam Head |
| 44070ESD | 3.2"(8.0 cm) ESD Handle,
0.13" (3.3 mm), Conical Foam Head |

TYPICAL APPLICATIONS

Conical Sealed Foam Swabs can be used for:

- Removing Contamination from Disk Drives
- Micro Mechanical Cleaning
- Cleaning & Removing Excess Adhesives & Chemical Residues
- Remove flux residue from Printed Circuit Boards

COMPATIBILITY

Polyurethane Foam Heads are compatible with most common solvents such as isopropyl alcohol and methanol. Not recommended for use with ketones such as acetone or methyl ethyl ketone.

Polypropylene, ESD Handles are compatible with most common solvents and dilute or weak acids.

COVENTRY™ Clean Room Products
Division of Chemtronics
8125 Cobb Center Drive
Kennesaw, GA 30152 USA
1-770-424-4888

REV. A (08/13)

TECHNICAL HOT LINE 1-800-TECH-401

44070 Conical Swabs Test Data

Cleanliness Data

Head Material	Polyurethane Foam	
Swab <input type="checkbox"/>	44070	44070I
Head Diameter	0.13" (3.3 mm)	0.13" (3.3 mm)
Handle Length	3.2" (8.0 cm)	3.2" (8.0 cm)
Particles:		
0.5 - 1 um	1,867	897
1.0 - 3 um	336	183
3.0 - 5 um	71	54
5.0 - 10 um	31	33
10 - 25 um	15	19
over 25 um	2	1
TOTAL	2,322	1,186
Chlorides (ug/swab)	0.21	None Detected

ESD Handles

44070ESD

<input type="checkbox"/>	<i>ESD Handles</i>
Surface Resistivity	10 ¹⁰ ohms/sq
Material	Polypropylene/Static Dissipative Copolymer Blend
Color	Blue

The ESD handles do not contain silicone, amides, or static dissipative coatings. The proprietary copolymer blend is not humidity dependent. The handles have excellent chemical compatibility, even in acetone.

The swabs were tested by Particle Measurement Technology. All the swabs tests were done using the recommended practices of the Institute of Environmental Science, Swabs and Wipes Working Group.

TECHNICAL AND APPLICATION ASSISTANCE

Coventry™ Clean Room Products provides a technical hotline to answer your technical and application related questions.

The toll free number is: **1-800-TECH-401**

Chemtronics® is a registered trademark of Chemtronics. All rights reserved. Coventry™ is a trademark of Chemtronics. All rights reserved.

DISTRIBUTED BY:

TECHNICAL HOT LINE 1-800-TECH-401