



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## 4600 Staticide® Ultra Floor Finish

### High Quality, High Performance

No other ESD floor finish can match Staticide® Ultra Floor Finish for electrical properties, physical longevity, and gloss. This urethane-enhanced formula features superior abrasion resistance and durability, fortifying floors with a long-lasting protective layer that is shiny and ESD-safe for 12 to 24 months.

By maximizing stripping cycles, companies can keep costs down by eliminating annual labor fees and production shut-downs.

Staticide® Ultra Floor Finish is the perfect choice for any environment where static control is required, such as electronic, medical, and clean room manufacturing facilities. With an average surface resistivity of  $10^8$  -  $10^9$  ohms per square, Staticide® Ultra Floor Finish fulfills ANSI/ESD S20.20 guidelines and is suitable for sensitive device manufacturing.

This water-based formula is UL listed for slip resistance, RoHS compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, acids, and ammonia.

**Directions:** Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

**Maintenance:** Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

*Product #4600-1; 4 gallons per case  
Product #4600-5; 5-gallon pail  
Product #4600-2; 54-gallon drum*

- ❖ **Coverage: 1,500 - 2,000 square feet per gallon**
- ❖ **Non-toxic; biodegradable**
- ❖ **Solids: 20 ± 5%**
- ❖ **Strip cycle: 12-24 months**
- ❖ **Suitable to use on vinyl, linoleum, and ceramic tile**
- ❖ **Surface resistivity:  $10^8$  –  $10^9$  ohms per square (average)**
- ❖ **Low V.O.C.**
- ❖ **Water-based polyurethane**

