



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## ESD High Temp Polyimide Tape

*Used in applications masking PCB gold features for wave soldering and IR reflow ovens*



Tape is wound on a plastic core.

- Removal leaves little or no residue
- Static charge generation during unwind and peel off stainless steel plate application is 5 volts @ 50% RH
- 1.0 mil thick (0.001" or 0.0254 mm) Polyimide Film (DuPont Kapton® or equivalent)
- 1.4 mil thick (0.0014" or 0.0356 mm) conductive polysiloxide adhesive
- Adhesive surface resistivity 10E3 to 10E4 ohms
- Max Temperature 260°C (500°F)
- For best results, apply to board using a rubber roller

Width

| Tape                    | 0.25"                 | 0.5"                  | 0.75"                 | 1"                    | Core | Length |
|-------------------------|-----------------------|-----------------------|-----------------------|-----------------------|------|--------|
| ESD High Temp Polyimide | <a href="#">47026</a> | <a href="#">47027</a> | <a href="#">47028</a> | <a href="#">47029</a> | 3"   | 36 yd  |

Width tolerance  $\pm 1/32"$

### Wescorp Tape Storage and Limited Warranty:

The user must determine the suitability for use of an antistatic tape for his particular application. For best results, tape inventory should be continually replenished. It is recommended that rolls of tape be stored flat and rotated (flipped over to the other side) periodically. Tapes should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Tape should not be stored in ultraviolet sunlight, moisture, or heat. Tape over one year old should be evaluated by the user to determine acceptability for the user's application. Protektive Pak recommends those tracking useful life of product to use shipping/invoice date as Protektive Pak expressly warrants that for a period of one (1) year from the date of purchase, our Wescorp Brand Antistatic Tape will be free of defects in material (parts) and workmanship (labor). See details of limited warranty online at [ProtektivePak.com](http://ProtektivePak.com).

Tape widths are nominal metric  $\pm 0.8$  mm ( $\pm 1/32"$ ).

1/4" is 6 mm nominal or 0.236"  
 1/2" is 12 mm nominal or 0.472"  
 3/4" is 18 mm nominal or 0.709"  
 1" is 24 mm nominal or 0.945"

### RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at [ProtektivePak.com](http://ProtektivePak.com)

Specifications and procedures subject to change without notice.

\*Wescorp is a Desco Industries brand.

### WESCORP\* ESD HIGH TEMP POLYIMIDE TAPE, PLASTIC CORE

# PROTEKTIVE PAK

PROTEKTIVE PAK  
 13520 MONTE VISTA AVENUE, CHINO, CA 91710  
 PHONE (909) 627-2578, FAX (909) 363-7331  
[ProtektivePak.com](http://ProtektivePak.com)

DRAWING NUMBER  
 47026

DATE:  
 March  
 2012