



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Vinyl Tape

472

Technical Data

February, 2011

Product Description 3M™ Vinyl Tape 472 is comprised of a heavy duty black vinyl backing with a black pigmented rubber adhesive. The thick vinyl backing makes it ideal for applications requiring both abrasion resistance and the inherent conformability of vinyl. The rubber adhesive has good instant adhesion and sticks well to a variety of surfaces.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Vinyl	Pigmented rubber	Black	36 yds. (33 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	23 oz./in. width (25 N/100 mm)	D-3330
Tensile Strength at Break:	32 lbs./in. width (560 N/100 mm)	D-3759
Elongation at Break:	270%	D-3759
Backing Thickness:	9.0 mils (0.23 mm)	D-3652
Total Tape Thickness:	10.4 mils (0.26 mm)	D-3652
Temperature Use Range:	Up to 225°F (107°C)	

Features

- Best results are attained when applied to clean, dry surface at temperatures between 60° to 80°F (16° to 27°C).
- Thick backing is ideal where heavy abrasion is anticipated.
- Temperature resistance to 225°F (107°C).
- Pigmented adhesive will stain some surfaces. Testing by the user is recommended to determine suitability in the proposed application.
- Resists most common solvents, care should be taken to avoid ketones, chlorinated hydrocarbons, and esters, found in lacquer thinners, degreasers, paint strippers, etc. which may cause the backing to swell or curl.
- Can be used in outdoor applications with clean removal from many surfaces up to 6 months.
- Stays on outdoors for up to a year.

3M™ Vinyl Tape

472

-
- Application Ideas**
- Heavy duty protection and abrasion resistance.
 - Splicing and patching.
 - Outdoor sealing, protecting, and marking.
 - Dissimilar metal separation.
 - Sealing barrier films and containers.
 - Sand blast and bead blast overspray protection.

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 18 months from date of manufacture.

Technical Information The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2008

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2011 70070950178 (2/11)