



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Autorange Digital Multimeter (MS8217)

Part # 480-001P

Hide Details

- 4000 counts
- Diode test/Buzzer
- Temperature Test
- Frequency/Duty Cycle
- Relative Measurement
- Data Hold
- Auto Power Off
- Auto/Manual Ranging
- Holster (secondary injection)
- Mechanical/Electronic Protection System
- In conformity with IEC 1010 CAT II 1000V
- Convenient Fuse/Battery Change Design
- Battery Life up to 500 Hours
- Lifetime Warranty

Built ruggedly for everyday use, the MS8217 digital multimeter is perfect for reliable & stable electrical testing.

SPECIFICATIONS:

DC Voltage range :	0.1mV-1000V
DC Voltage accuracy:	± (0.5%+3digits)
DC Current range:	0.1 μ A-10A
DC Current accuracy:	± (1.5%+3digits)
AC Voltage range:	0.1mV-1000V
AC Voltage accuracy:	± (1.0%+3digits)
AC Voltage Freq. response:	40Hz-500Hz
AC Current range:	0.1 μ A-10A
AC Current accuracy:	± (1.5%+3digits)
AC Current Freq. response:	40Hz-200Hz
Resistance range:	0.1Ω-40MΩ
Resistance accuracy:	± (0.5%+2digits)
Capacitance range:	0.01nF-100μF
Capacitance accuracy:	± (3.0%+5digits)
FREQUENCY/DUTY CYCLE Range:	10Hz-100kHz
FREQUENCY/DUTY CYCLE Accuracy:	± (0.1%+3digits)
TEMPERATURE Range:	-55°C-1000°C
TEMPERATURE Accuracy:	± (2.0%+1°C)

