



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






## 3 Phase 25 Amp Rectifier Bridge

Qualified per MIL-PRF-19500/483

Qualified Level:  
JANTX

### DESCRIPTION

This series of high-current three-phase bridge rectifiers are constructed with hermetically sealed rectifiers built with the same design and construction techniques used in military applications for the upmost in reliability. These include voidless glass encapsulation and internal "Category 1" metallurgical bonds. They can optionally be purchased built with diodes that have been screened and mil-qualified to MIL-PRF-19500/483, making them ideal for applications where failure cannot be tolerated. These 25A rectifier bridges are available with working peak reverse voltage ratings of 200, 400, 600, or 800 V per leg.



ME Package

**Important:** For the latest information, visit our website <http://www.microsemi.com>.

### FEATURES

- Voidless hermetically sealed glass packages used internally for each leg.
- Triple-layer passivation.
- Internal "Category 1" metallurgical bonds.
- JANTX qualification available per MIL-PRF-19500/483.  
(See [part nomenclature](#) for all available options).
- RoHS compliant versions available without Sn/Pb solder dip.

### APPLICATIONS / BENEFITS

- Conversion of three phase ac to dc current flow.
- Working peak reverse voltages 200 to 800 volts.
- Military and other high-reliability applications.
- High forward surge current capability.
- Low thermal resistance.
- Extremely robust construction.
- Inherently radiation hard as described in Microsemi [MicroNote 050](#).

### MAXIMUM RATINGS @ 25 °C unless otherwise noted

| Parameters/Test Conditions   | Symbol         | Value         | Unit   |
|--|----------------|---------------|--------|
| Junction Temperature   | $T_J$          | -65 to +175   | °C     |
| Storage Temperature  | $T_{STG}$      | -65 to +150   | °C     |
| Working Peak Reverse Voltage   | $V_{RWM}$      | 483-01<br>200 | V (pk) |
|  |                | 483-02<br>400 |        |
|  |                | 483-03<br>600 |        |
|  |                | 483-04<br>800 |        |
| Maximum Average DC Output Current @ $T_C = +55\text{ °C}$                              | $I_{O1}^{(1)}$ | 25            | A      |
| Maximum Average DC Output Current @ $T_C = +100\text{ °C}$                             | $I_{O2}^{(2)}$ | 18.5          | A      |
| Forward Surge Current @ $I_O = I_{O1}$ , $T_C = +55\text{ °C}$ , $t_p = 8.3\text{ ms}$ | $I_{F(surge)}$ | 150           | A (pk) |
| Solder Temperature @ 10 s  | $T_{SP}$       | 260           | °C     |

- Notes:**
1. Derate from 25 A at  $T_C = +55\text{ °C}$  to 18.5 A at  $T_C = +100\text{ °C}$  (144 mA dc/ °C).
  2. Derate from 18.5 A at  $T_C = +100\text{ °C}$  to 0 A at  $T_C = +150\text{ °C}$  (370 mA dc/ °C).

#### MSC – Lawrence

6 Lake Street,  
Lawrence, MA 01841  
Tel: 1-800-446-1158 or  
(978) 620-2600  
Fax: (978) 689-0803

#### MSC – Ireland

Gort Road Business Park,  
Ennis, Co. Clare, Ireland  
Tel: +353 (0) 65 6840044  
Fax: +353 (0) 65 6822298


#### Website:

[www.microsemi.com](http://www.microsemi.com)



**MECHANICAL and PACKAGING**

- CASE: Epoxy filled aluminum case with hermetically sealed void-less hard glass rectifiers with tungsten slugs.
- TERMINALS: Nickel plated brass with optional hot tin-lead solder dip. **NOTE:** Solder dip will eliminate RoHS compliance.
- MARKING: Part number on one side of case.
- POLARITY: Marked on body adjacent to terminals (see terminal polarity marking on last page).
- WEIGHT: Approximately 32 grams.
- See [Package Dimensions](#) on last page.

**PART NOMENCLATURE**

**SYMBOLS & DEFINITIONS**

| Symbol     | Definition  |
|------------|---|
| $V_{(BR)}$ | Minimum Breakdown Voltage: The minimum voltage the device will exhibit at a specified current.  |
| $V_{RWM}$  | Working Peak Reverse Voltage: The maximum peak voltage that can be applied over the operating temperature range excluding all transient voltages (ref JESD282-B). Also sometimes known as PIV.                                  |
| $I_O$      | Average Rectified Output Current: The output current averaged over a full cycle with a 50 Hz or 60 Hz sine-wave input and a 180 degree conduction angle.  |
| $V_F$      | Maximum Forward Voltage: The maximum forward voltage the device will exhibit at a specified current.  |
| $I_R$      | Maximum Reverse Current: The maximum reverse (leakage) current that will flow at the specified voltage and temperature.   |
| $t_{rr}$   | Reverse Recovery Time: The time interval between the instant the current passes through zero when changing from the forward direction to the reverse direction and a specified decay point after a peak reverse current occurs. |


**ELECTRICAL CHARACTERISTICS**

| PART NUMBER | MINIMUM BREAKDOWN VOLTAGE Per Leg $V_{(BR)}$ @ $I_R = 50 \mu A$ | MAXIMUM REVERSE CURRENT PER LEG $I_R @ V_{RWM}$ |                      |                     | FORWARD VOLTAGE $V_F$ $I_F @ 39 A$ (pk) @ 8.3 ms Duty Cycle $\leq 2\%$ | REVERSE RECOVERY $t_{rr}$ (Note 1) |
|-------------|---|---|----------------------|---------------------|--|------------------------------------|
|             |   | $T_C = +25^\circ C$                             | $T_C = +100^\circ C$ | $T_A = -55^\circ C$ |  |                                    |
|             |   | Volts   | $\mu A$              | $\mu A$             |  |                                    |
| 483-01      | 220   | 1.0   | 200                  | 2.0                 | 1.3  | 2.5                                |
| 483-02      | 440   | 1.0   | 200                  | 2.0                 | 1.3  | 2.5                                |
| 483-03      | 660   | 1.0   | 200                  | 2.0                 | 1.3  | 2.5                                |
| 483-04      | 880   | 1.0   | 200                  | 2.0                 | 1.3  | 2.5                                |


**NOTE 1:**  $I_F = 0.5 A$ ,  $I_R = 1.0 A$ ,  $I_{R(REC)} = 0.250 A$ .

**NOTE 4:** Point at which  $T_C$  is referenced shall be in metal part of case as shown in [package dimensions](#) drawing on last page.

**GRAPHS**




**FIGURE 1**  
Typical Forward Voltage Per Leg vs. Forward Current




**FIGURE 2**  
Typical Leakage Current vs. PIV

GRAPHS



**FIGURE 3**  
Current Derating Curve

**PACKAGE DIMENSIONS**


| Dimensions     |        |       |             |       |                |        |       |             |       |
|----------------|--------|-------|-------------|-------|----------------|--------|-------|-------------|-------|
| Ltr            | Inches |       | Millimeters |       | Ltr            | Inches |       | Millimeters |       |
|                | Min    | Max   | Min         | Max   |                | Min    | Max   | Min         | Max   |
| A              | 0.710  | 0.770 | 18.03       | 19.56 | L <sub>1</sub> | 0.130  | 0.320 | 3.30        | 8.13  |
| B              | 0.355  | 0.395 | 9.02        | 10.03 | L <sub>2</sub> | 0.015  | 0.030 | 0.38        | 0.76  |
| C              | 0.355  | 0.395 | 9.02        | 10.03 | L <sub>3</sub> | 0.100  | 0.125 | 2.54        | 3.18  |
| D <sub>1</sub> | 0.141  | 0.151 | 3.58        | 3.84  | M              | 0.040  | 0.060 | 1.02        | 1.52  |
| D <sub>2</sub> | 0.108  | 0.118 | 2.74        | 3.00  | N              | 0.720  | 0.780 | 18.29       | 19.81 |
| E              | 0.355  | 0.395 | 9.02        | 10.03 | O              | 1.84   | 1.90  | 46.74       | 48.26 |
| F              | 0.230  | 0.270 | 5.84        | 6.86  | P              | 2.22   | 2.28  | 56.39       | 57.91 |
| G              | 0.149  | 0.189 | 3.78        | 4.80  | R              | 0.090  | 0.150 | 2.29        | 3.81  |
| H              | 0.355  | 0.395 | 9.02        | 10.03 | S              | 0.168  | 0.208 | 4.27        | 5.28  |
| J              | -      | 0.820 | -           | 20.83 | T              | 1.47   | 1.53  | 37.34       | 38.86 |
| K              | 0.390  | 0.590 | 9.91        | 14.99 |                |        |       |             |       |

**NOTES:**

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Polarity shall be marked as shown on drawing.
4. Point at which T<sub>C</sub> is read shall be in metal part of case as shown on drawing.
5. In accordance with ASME Y14.5M, diameters are equivalent to  $\Phi$ x symbology.

See schematic on next page.

**SCHEMATIC**

