imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HUMIDITY INDICATOR CARDS

An integral part of a complete moisture barrier packaging assembly is the Humidity Indicator Card. High relative humidity can cause significant, possibly irreparable damage to sensitive equipment, supplies, and products. To ensure dehydration measures work, humidity indicator cards measure the relative humidity (RH) inside sealed packages to allow immediate visual inspection of whether it has sustained unsafe humidity levels.

The Monitor Card contains chemically impregnated, humidity sensitive, indicating spots that will change color with moisture. The comparison bar is used to determine relative humidity of air. Select the indicating spot that most closely matches the color of the comparison bar. The measured relative humidity is the percentage indicated on the matching spot. The chemical reaction of the indicating spots is completely reversible; the spots will continue to change color as the moisture levels change.

Humidity Monitor cards are sold in cans. The 2" x 3" blotting paper cards indicate relative humidity. Humidity Indicator Cards should be inserted and sealed within an MBB bag with the desiccant packs.

| ltem# | Unit Size | Std. Package | Relative Humidity |
|-------|--------------|----------------|-------------------|
| 48886 | 2" x 3" Card | 125 pieces/can | 5/10/15 |
| 48885 | 2" x 3" Card | 125 pieces/can | 5/10/60 |
| 48882 | 2" x 3" Card | 100 pieces/can | 10/20/30/40 |

The 48882, 48885, and 48886 humidity indicator cards meet the requirements of MIL-I-8835 and IPC/JEDEC J-STD-033A.

"Humidity Indicator Card (HIC) A card on which a moisture-sensitive chemical is printed such that it will change color from blue to pink when the indicated relative humidity is exceeded. This is packed inside the moisture-sensitive bag, along with the desiccant, to aid in determining the level of moisture to which the moisture-sensitive devices have been subjected." (IPC/JEDEC J-STD-033A section 1.5.7)

Application

- 1. The humidity indicator spots will change from blue (dry condition) to pink (humid condition) as the relative humidity changes in the volume of air surrounding the indicator.
- 2. Relative humidity is indicated at the lavender color.
- 3. Indicator spots will change within eight hours of being exposed to a change in relative humidity.

- 4. The humidity indicator spots are reversible, and the pink spots will change back to blue when the volume of air is dried. Humidity indicator cards with pink or lavender spots can be returned to a blue color by placing indicators in a sealed container with 33 grams (1 unit) of desiccant for four hours.
- 5. The highest humidity indicator spot should be blue before being put into use.
- 6. The humidity indicator will be at its most accurate at a temperature of 23 °C (73 °F).
- 7. Avoid contact with indicator spots. Wash any irritated areas with clean water.

Handling

- 1. Store humidity indicators in original container with desiccant when possible and keep sealed. Never reuse a indicator card if it has already changed color.
- 2. Replace desiccant bag after three openings of container.
- 3. Store in dry, cool area.
- 4. Keep indicators out of direct sunlight.
- 5. Keep humidity indicators away from water or steam.
- 6. Ammonia gases will damage humidity indicators.



DATE:

July

2008



Made in America

| Material Safety Data Sheet NFPA Designation 704 | | | | | 6. ACCIDENTAL RELEASE MEASURES | | | | | |
|---|--------------|----------------------------|----------------|--|---|-----------|------------------------|--|----------------|--|
| May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200. Standard must be consulted for specific requirements. Degree of Hazard: 4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant | | | | | Environmental precautions: Methods for cleaning up: | | Take up o load into | Do not flush into surface water or sanity sewer system Take up contaminated material by mechanical means, load into clean containers, and dispose of in accordance with legal regulations | | |
| 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING | | | 7 | 7. HANDLING AND STORAGE | | | | | | |
| Product information COMMERCIAL PRODUCT NAME: REVERSIBLE HUMIDITY INDICATOR COMPANY: Desco 3651 Walnut Ave. | | | | Handling Safe handling advice: No special precautions required Storage | | | 1 | | | |
| PHONE: (909) 627-8178 FAX: (909) 627-7449 | | | | Requirement for storage area and containers: Keep in a dry place | | | | | | |
| | (303) 027-74 | | | - 8 | . EXPOSURE C | ONTROLS/ | PERSONAL | PROTECTION | | |
| 2. COMPOSITION/INFORMATION ON INGREDIENTS Chemical nature: Cobalt dichloride on cardboard | | | c | Components with workplace parameters | | | | | | |
| Components CAS-No. | Symbol(s) | R-phrase(s) | Concentration | | Components | CAS-No. | Value | Remarks | Basis | |
| cobalt(II) chloride 7646-79-9 | T, N | R49, R22, R42/43 R50-53 | >0.10 - <1.00% | | cobalt | 7440-48-4 | 0.5 mg/m3 | Inhalable dust. Sensitizer | TRGS900 TRK | |
| 3. HAZARDS IDENTIFICATION None under normal use 4. FIRST AID MEASURES General advice: None | | | | Personal protective equipmentRespiratory protection:N.A.Hand protection:Protective glovesEye protection:N.A.Skin and body protection:Not requiredHygiene measures:Wash off with warm water and soapProtective measures:Prophylactic use of protective ointment (barrier cream) is recommended. | | | | | | |
| Eye contact: Rinse immediately with plenty of water, also under the | | | | 9 | 9. PHYSICAL AND CHEMICAL PROPERTIES | | | | | |
| eyelids, for at least 15 minutesSkin contact:Wash off with soap and plenty of waterInhalation:N.A. | | | | Appearance | | | | | | |
| Ingestion: Rinse mouth Notes to physician | | | | C | Form: Plates Color: Pink to blue Odor: None | | | | | |
| Treatment: | None | | | | Other data | | | | | |
| 5. FIRE-FIGHTING MEASURES | | | v | Water solubility: Partly soluble, max. 600 ppm CoCl2 can be lear | | | oCl2 can be leached | | | |
| Suitable extinguishing media: Use extinguishing measures appropriate to the envirn. | | | р | out pH: 4.5 - 6 | | | | | | |
| Extinguishing media which must not be used for safety reasons: None | | | | | | | | | | |
| | | | | | | | | | | |

| 10. STABILITY AND REACTIV | ΊΤΥ | 14. TRANSPORT INFORMATION | | | |
|--|---|---|---|--|--|
| Hazardous reactions: hygrosco (Conditions to avoid) | opic | Land transport: | Not classified as dangerous in the meaning of transport regulations. | | |
| Hazardous reactions: Alkali me (Materials to avoid) | etals | Sea transport: | Not classified as dangerous in the meaning of transport regulations. | | |
| Information about decomposition: No deco | | | Not classified as dangerous in the meaning of transport regulations. | | |
| 11. TOXICOLOGICAL INFORM | IATION | 15. REGULATORY INFORMATION | | | |
| Acute toxicity | | General advice: The product does not need to be labeled in | | | |
| Acute oral toxicity: | LD50 Dose: 766mg/kg | | accordance with EC directives or respective national laws. | | |
| | (cobalt (II)chloride-hexahydrate) | Hazardous components which must be listed on the label: | | | |
| Irritation, Sensitization, Other Dat | ta Toxicology | Preparation: Other information: | Not applicable Follow the usual precautions required when handling chemicals. | | |
| Sensitization: Repeated dose toxicity: | Result: May cause sensitization by skin contact. No data available | | chemicals. | | |
| | | 16. OTHER INFORMATION | | | |
| 12. ECOLOGICAL INFORMAT | ION | Responsible for SDS: Environmental Protection Contact person: Dep. CEQ Tel.08761/82-654 | | | |
| Decomposition: | Not readily biodegradable | The information presented herein is believed to be accurate, but is not warranted. | | | |
| Ecotoxicity effects | | It does not represent any assurance of properties of the product. The specifications are to be drawn from the corresponding leaflet. | | | |
| Further information: Ecotoxicity | No data available | A vertical bar () in the left margin indicat | tes an amendment from the previous version. | | |
| Heavy metals: | Heavy metals should not be released into the environment. | Legend | | | |
| Additional information about ecology: | Heavy metals should not be released into the environment | N.A.: N.AV.: N.R.: | Not applicable Not Available Not relevant | | |
| 13. DISPOSAL CONSIDERATI | IONS | | | | |
| Product: | Dispose as special waste. Can be landfilled or incinerated, when in compliance with the Environmental Protection (Duty of Care) Regulations 1991. | RoHS Compliance Statement None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at <u>ProtektivePak.com</u> . | | | |