



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**SXB/SXE SERIES**
**SLE/SZE SERIES**
**◆FEATURES**

- SXB:Standard
- SXE:Low ESR
- SLE:Low Profile,Low ESR
- SZE:Low Profile,Ultra Low ESR
- RoHS Compliance
- Lead free reflow soldering is available(260°C,10sec):(Available for MSL3)


**◆SPECIFICATIONS**

Series	SXB	SXE	SLE	SZE
	1.9mm		1.4mm	
Temperature Range(°C)	-55~+105°C			
Rated Voltage Range(V.DC)	2~10	2~6.3	2~6.3	2, 2.5
Capacitance Range(μF)	22~220	33~220	47~100	100~150
Capacitance Tolerance(20°C , 120Hz)	±20%			
Leakage Current(μA/after 5 minutes)	≤0.04CV			
Dissipation Factor(20°C , 120Hz) (tanδ)	≤0.1			
Equivalent Series Resistance(ESR) (mΩ/20°C , 100kHz)	13~30	7~9	9	5
Maximum Allowable Ripple Current(mA r.m.s/100kHz)	1,600~ 3,000	3,000	3,000	3,000
Surge Voltage	Rated voltage ×1.25			
Endurance (105°C, 2000hrs, Rated Voltage applied)	ΔC	Within ±20% of the initial value		
	tanδ	≤200% of initial specified value		
	LC	≤initial specified value		
Damp heat(Steady state) (60°C, 90%RH, 500hrs, No-applied voltage)	ΔC	Within -20~+40% of the initial value	Within -20~+60% of the initial value	
	tanδ	≤200% of initial specified value		
	LC	≤300% of initial specified value		

**◆STANDARD SIZE**

Series	WV(V.DC)	Cap( $\mu$ F)	Size(mm)			ESR(m $\Omega$ )	(mAr.m.s)	Part No.
			L	W	H			
SXB	2(d)	100	7.3	4.3	1.9	13	3,000	2SXB100M
		150	7.3	4.3	1.9	13	3,000	2SXB150M
		220	7.3	4.3	1.9	13	3,000	2SXB220M
	2.5(e)	82	7.3	4.3	1.9	13	3,000	2.5SXB82M
		100	7.3	4.3	1.9	13	3,000	2.5SXB100M
		120	7.3	4.3	1.9	13	3,000	2.5SXB120M
		150	7.3	4.3	1.9	13	3,000	2.5SXB150M
		180	7.3	4.3	1.9	13	3,000	2.5SXB180M
		220	7.3	4.3	1.9	13	3,000	2.5SXB220M
		4(g)	68	7.3	4.3	1.9	13	3,000
	100		7.3	4.3	1.9	13	3,000	4SXB100M
	150		7.3	4.3	1.9	13	3,000	4SXB150M
	6.3(j)	22	7.3	4.3	1.9	13	3,000	6SXB22M
		33	7.3	4.3	1.9	13	3,000	6SXB33M
		47	7.3	4.3	1.9	13	3,000	6SXB47M
		68	7.3	4.3	1.9	13	3,000	6SXB68M
		100	7.3	4.3	1.9	18	3,000	6SXB100M
	8(k)	33	7.3	4.3	1.9	18	2,500	8SXB33M
		47	7.3	4.3	1.9	18	2,500	8SXB47M
	10(A)	22	7.3	4.3	1.9	30	1,600	10SXB22M
SXE	2(d)	100	7.3	4.3	1.9	9	3,000	2SXE100M
		150	7.3	4.3	1.9	9	3,000	2SXE150M
		180	7.3	4.3	1.9	9	3,000	2SXE180M
		220	7.3	4.3	1.9	9	3,000	2SXE220M
		220	7.3	4.3	1.9	7	3,000	2SXE220MR07
	2.5(e)	82	7.3	4.3	1.9	9	3,000	2.5SXE82M
		100	7.3	4.3	1.9	9	3,000	2.5SXE100M
		120	7.3	4.3	1.9	9	3,000	2.5SXE120M
		150	7.3	4.3	1.9	9	3,000	2.5SXE150M
		180	7.3	4.3	1.9	9	3,000	2.5SXE180M
		220	7.3	4.3	1.9	9	3,000	2.5SXE220M
		220	7.3	4.3	1.9	7	3,000	2.5SXE220MR07
	4(g)	68	7.3	4.3	1.9	9	3,000	4SXE68M
		82	7.3	4.3	1.9	9	3,000	4SXE82M
		100	7.3	4.3	1.9	9	3,000	4SXE100M
		120	7.3	4.3	1.9	9	3,000	4SXE120M
		150	7.3	4.3	1.9	9	3,000	4SXE150M
	6.3(j)	33	7.3	4.3	1.9	9	3,000	6SXE33M
		47	7.3	4.3	1.9	9	3,000	6SXE47M
		68	7.3	4.3	1.9	9	3,000	6SXE68M
82		7.3	4.3	1.9	9	3,000	6SXE82M	
100		7.3	4.3	1.9	9	3,000	6SXE100M	
SLE	2(d)	100	7.3	4.3	1.4	9	3,000	2SLE100M
	2.5(e)	82	7.3	4.3	1.4	9	3,000	2.5SLE82M
	4(g)	68	7.3	4.3	1.4	9	3,000	4SLE68M
	6.3(j)	47	7.3	4.3	1.4	9	3,000	6SLE47M
SZE	2(d)	100	7.3	4.3	1.4	5	3,000	2SZE100M
		150	7.3	4.3	1.4	5	3,000	2SZE150M
	2.5(e)	100	7.3	4.3	1.4	5	3,000	2.5SZE100M
		120	7.3	4.3	1.4	5	3,000	2.5SZE120M