



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Surface Mount Type

POSCAP

Series : TC



Features

- Guaranteed at 125 °C
- RoHS compliance, Halogen free

Specifications

Size code	D2E	D3L	D4
Category temperature range	-55 °C to +125 °C		
Rated voltage range	4 V.DC to 6.3 V.DC	2.5 V.DC to 10 V.DC	
Category voltage range	3.2 V.DC to 5.0 V.DC	2.0 V.DC to 8.0 V.DC	
Rated capacitance range	100 µF to 330 µF	150 µF to 680 µF	330 µF to 1000 µF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)		
Leakage current	Please see the attached characteristics list		
Dissipation factor (tan δ)	Please see the attached characteristics list		
Surge voltage (V.DC)	Rated voltage × 1.15		
Endurance	+125 °C, 1000 h Category temperature range voltage applied		
	Capacitance change	Within ±20 % of the initial value	
	tan δ	≤ 2 times of the initial limit	
	DC leakage current	≤ 2 times of the initial limit	
Damp heat (Steady State)	+60 °C, 90 % to 95 %, 500 h, No-applied voltage		
	Capacitance change	Within +50 %, -20 % of the initial value (ETCF1000M6H (5H))	
	tan δ	≤ 1.5 times of the initial limit	
	DC leakage current	≤ 3 times of the initial limit	

Marking

R. Voltage (VDC)	2.5	4.0	6.3	10.0
Code	e	g	j	A

Dimensions (not to scale)

Unit : mm

Size code	L±0.3	W±0.2	H±0.2*1	S±0.2	W1±0.1
D2E	7.3	4.3	1.8	1.3	2.4
D3L	7.3	4.3	2.8	1.3	2.4
D4	7.3	4.3	3.8	1.3	2.4

* Externals of figure are the reference.
* 1 ±0.1 : D2E

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		Floor life	
						L	W	H		Ripple* ¹ current (mA r.m.s.)	ESR* ² (mΩ max.)	tan δ* ³	LC* ⁴ (μA)	Part number	Min. Packaging Qty (pcs)	Reflow Temp ≤ 260°C	Reflow Temp ≤ 250°C
TCE	2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	3500	12	0.10	170.0	ETCE680MCL	2500	3	2a
		105	2.0	125		7.3	4.3	2.8		3100	15	0.10	170.0	ETCE680MFL	2500		
		105	2.0	125	1000	7.3	4.3	3.8	D4	3900	15	0.15	250.0	ETCE1000MF	2000		
	4	105	3.2	125	150	7.3	4.3	1.8	D2E	2800	18	0.10	60.0	4TCE150MI	3000		
										3100	15	0.10	88.0	4TCE220MF	3000		
		220	2800	18	0.10	88.0	4TCE220MI	3000									
			2400	25	0.10	88.0	4TCE220M	3000									
		330	2800	18	0.10	132.0	4TCE330MI	3000									
			2400	25	0.10	132.0	4TCE330M	3000									
		470	105	3.2	125	7.3	4.3	2.8	D3L	3500	12	0.10	188.0	4TCE470MCL	2500		
										3100	15	0.10	188.0	4TCE470MFL	2500		
			2800	18	0.10	188.0	4TCE470MIL	2500									
										2400	25	0.10	188.0	4TCE470ML	2500		
	6.3	105	5.0	125	100	7.3	4.3	1.8	D2E	2800	18	0.10	63.0	6TCE100MI	3000		
										2400	25	0.10	63.0	6TCE100M	3000		
										3100	15	0.10	94.5	6TCE150MF	3000		
			150	2800	18	0.10	94.5	6TCE150MI		3000							
				2400	25	0.15	94.5	6TCE150M		3000							
			220	2800	18	0.15	138.6	6TCE220MI		3000							
		2400		25	0.15	138.6	6TCE220M	3000									
		330	105	5.0	125	7.3	4.3	2.8	D3L	3100	15	0.10	207.9	6TCE330MFL	2500		
										2800	18	0.10	207.9	6TCE330MIL	2500		
										2400	25	0.10	207.9	6TCE330ML	2500		
			470	3500	18	0.15	296.1	6TCE470MI		2000							
				3000	25	0.15	296.1	6TCE470M		2000							
	3500			18	0.15	428.4	6TCE680MI	2000									
	680	105	5.0	125	7.3	4.3	3.8	D4	3000	25	0.15	428.4	6TCE680M	2000			
									3000	25	0.15	428.4	6TCE680M	2000			
10	105	8.0	125	220	7.3	4.3	2.8	D3L	2800	18	0.10	220.0	10TCE220MIL	2500			
									2400	25	0.10	220.0	10TCE220ML	2500			
								D4	3000	25	0.10	330.0	10TCE330M	2000			
TCF	2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	4400	6	0.10	170.0	ETCF680M6L	2500	3	
										4400	7	0.10	170.0	ETCF680M7L	2500		
										4400	10	0.10	170.0	ETCF680ML	2500		
		1000	7.3	4.3	3.8	D4	6100	5	0.10	170.0	ETCF680M5H	2000					
							6100	5	0.10	250.0	ETCF1000M5H	2000					
							5600	6	0.10	250.0	ETCF1000M6H	2000					
	4	105	3.2	125	330	7.3	4.3	2.8	D3L	4000	12	0.10	132.0	4TCF330ML	2500		
										4400	10	0.10	188.0	4TCF470ML	2500		
										4400	10	0.10	272.0	4TCF680MAH	2000		
	6.3	105	5.0	125	220	7.3	4.3	2.8	D3L	6100	5	0.10	138.6	6TCF220M5L	2500		
										4600	9	0.10	138.6	6TCF220M9L	2500		
		330	4000	12	0.10	138.6	6TCF220ML	2500									
			3900	9	0.10	207.9	6TCF330M9L	2500									
		470	7.3	4.3	3.8	D4	4400	10		0.10	296.1	6TCF470MAH	2000				
	10	105	10.0	125	150	7.3	4.3	2.8	D3L	3600	15	0.10	150.0	10TCF150ML	2500		

*1 Ripple current (100 kHz/ +45 °C), *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".