



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!





Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





- 1 HOUSING: FLAME RETARDANT, GLASS FILLED, POLYESTER, COLOR: BLACK. CONTACT: PHOSPHOR BRONZE
- 2 CONTACT: DUPLEX PLATED 0.25µm[.000010] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] BRIGHT TIN-LEAD ON LEADS, ALL OVER 1.27µm[.000050] NICKEL
- 3 THESE DIMENSIONS PERTAIN TO CAVITY CENTERLINES ONLY - NOT TO CONTACT LOCATIONS
- 4 MARK PART NUMBER AND DATE CODE IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.
- 5 TOLERANCE IS NON-CUMULATIVE.
- 6 2 POSITION DATE CODE IS MARKED OPPOSITE SIDE OF TE CONNECTIVITY LOGO.
- 7 POINT-OF-MEASUREMENT DIMENSION FOR PLATING THICKNESS (INSIDE CONTACT BEAM).
- 8 POINT-OF-CONTACT DIMENSION.
- 9 TE CONNECTIVITY TRADEMARK AND CSA LOGO ARE MOLDED INTO HOUSING, THIS LOCATION.
- 10 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 11 CONTACT: DUPLEX PLATED 0.25µm[.000010] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] MATTE TIN ON LEADS, ALL OVER 1.27µm[.000050] MIN NICKEL
- 12 ROHS 2002/95/EC COMPLIANT.

LOC	DIST	P	LTR	REVISED	PER	ECO	DATE	DMN	APVD
12	11			96.52	[3.800]	99.06	[3.900]	78	9-535598-0
12	11			93.98	[3.700]	96.52	[3.800]	76	8-535598-9
12	11			91.44	[3.600]	93.98	[3.700]	74	8-535598-8
12	11			88.90	[3.500]	91.44	[3.600]	72	8-535598-7
12	11			86.36	[3.400]	88.90	[3.500]	70	8-535598-6
12	11			83.82	[3.300]	86.36	[3.400]	68	8-535598-5
12	11			81.28	[3.200]	83.82	[3.300]	66	8-535598-4
12	11			78.74	[3.100]	81.28	[3.200]	64	8-535598-3
12	11			76.20	[3.000]	78.74	[3.100]	62	8-535598-2
12	11			71.12	[2.800]	73.66	[2.900]	58	8-535598-1
12	11			68.58	[2.700]	71.12	[2.800]	56	8-535598-0
12	11			66.04	[2.600]	68.58	[2.700]	54	7-535598-9
12	11			63.50	[2.500]	66.04	[2.600]	52	7-535598-8
12	11			58.42	[2.300]	60.96	[2.400]	48	7-535598-7
12	11			55.88	[2.200]	58.42	[2.300]	46	7-535598-6
12	11			53.34	[2.100]	55.88	[2.200]	44	7-535598-5
12	11			50.80	[2.000]	53.34	[2.100]	42	7-535598-4
12	11			99.06	[3.900]	101.60	[4.000]	80	7-535598-3
12	11			73.66	[2.900]	76.20	[3.000]	60	7-535598-2
12	11			60.96	[2.400]	63.50	[2.500]	50	7-535598-1
12	11			48.26	[1.900]	50.80	[2.000]	40	7-535598-0
12	11			45.72	[1.800]	48.26	[1.900]	38	6-535598-9
12	11			43.18	[1.700]	45.72	[1.800]	36	6-535598-8
12	11			40.64	[1.600]	43.18	[1.700]	34	6-535598-7
12	11			38.10	[1.500]	40.64	[1.600]	32	6-535598-6
12	11			35.56	[1.400]	38.10	[1.500]	30	6-535598-5
12	11			33.02	[1.300]	35.56	[1.400]	28	6-535598-4
12	11			30.48	[1.200]	33.02	[1.300]	26	6-535598-3
12	11			27.94	[1.100]	30.48	[1.200]	24	6-535598-2
12	11			25.40	[1.000]	27.94	[1.100]	22	6-535598-1
12	11			22.86	[.900]	25.40	[1.000]	20	6-535598-0
12	11			20.32	[.800]	22.86	[.900]	18	5-535598-9
12	11			17.78	[.700]	20.32	[.800]	16	5-535598-8
12	11			12.70	[.500]	15.24	[.600]	12	5-535598-7
12	11			10.16	[.400]	12.70	[.500]	10	5-535598-6
12	11			7.62	[.300]	10.16	[.400]	8	5-535598-5
12	11			5.08	[.200]	7.62	[.300]	6	5-535598-4
12	11			2.54	[.100]	5.08	[.200]	4	5-535598-3
12	11	10				2.54	[.100]	2	5-535598-2
12	11			15.24	[.600]	17.78	[.700]	14	5-535598-1
2				96.52	[3.800]	99.06	[3.900]	78	4-535598-0
2				93.98	[3.700]	96.52	[3.800]	76	3-535598-9
2				91.44	[3.600]	93.98	[3.700]	74	3-535598-8
2				88.90	[3.500]	91.44	[3.600]	72	3-535598-7
2				86.36	[3.400]	88.90	[3.500]	70	3-535598-6
2				83.82	[3.300]	86.36	[3.400]	68	3-535598-5
2				81.28	[3.200]	83.82	[3.300]	66	3-535598-4
2				78.74	[3.100]	81.28	[3.200]	64	3-535598-3
2				76.20	[3.000]	78.74	[3.100]	62	3-535598-2
2				71.12	[2.800]	73.66	[2.900]	58	3-535598-1
2				68.58	[2.700]	71.12	[2.800]	56	3-535598-0
2				66.04	[2.600]	68.58	[2.700]	54	2-535598-9
2				63.50	[2.500]	66.04	[2.600]	52	2-535598-8
2				58.42	[2.300]	60.96	[2.400]	48	2-535598-7
2				55.88	[2.200]	58.42	[2.300]	46	2-535598-6
2				53.34	[2.100]	55.88	[2.200]	44	2-535598-5
2				50.80	[2.000]	53.34	[2.100]	42	2-535598-4
2				99.06	[3.900]	101.60	[4.000]	80	2-535598-3
2				73.66	[2.900]	76.20	[3.000]	60	2-535598-2
2				60.96	[2.400]	63.50	[2.500]	50	2-535598-1
2				48.26	[1.900]	50.80	[2.000]	40	2-535598-0
2				45.72	[1.800]	48.26	[1.900]	38	1-535598-9
2				43.18	[1.700]	45.72	[1.800]	36	1-535598-8
2				40.64	[1.600]	43.18	[1.700]	34	1-535598-7
2				38.10	[1.500]	40.64	[1.600]	32	1-535598-6
2				35.56	[1.400]	38.10	[1.500]	30	1-535598-5
2				33.02	[1.300]	35.56	[1.400]	28	1-535598-4
2				30.48	[1.200]	33.02	[1.300]	26	1-535598-3
2				27.94	[1.100]	30.48	[1.200]	24	1-535598-2
2				25.40	[1.000]	27.94	[1.100]	22	1-535598-1
2				22.86	[.900]	25.40	[1.000]	20	1-535598-0
2				20.32	[.800]	22.86	[.900]	18	535598-9
2				17.78	[.700]	20.32	[.800]	16	535598-8
2				12.70	[.500]	15.24	[.600]	12	535598-7
2	10			10.16	[.400]	12.70	[.500]	10	535598-6
2	10			7.62	[.300]	10.16	[.400]	8	535598-5
2	10			5.08	[.200]	7.62	[.300]	6	535598-4
2	10			2.54	[.100]	5.08	[.200]	4	535598-3
2	10					2.54	[.100]	2	535598-2
2				15.24	[.600]	17.78	[.700]	14	535598-1

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONS: mm. TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±, 1 PLC ±, 2 PLC ±, 3 PLC ±, 4 PLC ±, ANGLES ±.

DIN M. BINNER 06NOV2002
 CHK: J. JOLSON 06NOV02
 APVD: J. JOLSON 06NOV02

RECEPTACLE ASSEMBLY, MOD IV, DOUBLE ROW, DUAL ENTRY, .100X.100CL, VERTICAL MOUNT, AMPMODU

108-25022
 APPLICATION SPEC
 114-25018

SIZE: A1
 CASE CODE: 00779
 DRAWING NO: 535598

RESTRICTED TO: -
 WEIGHT: -
 CUSTOMER DRAWING

SCALE: 1:1
 SHEET: 1 OF 1
 REV: P5