



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING			5012W5812
CHEMINAX	50 OHM, AWG 12, 7 STRANDS OF AWG 20, WATERBLOCKED, OPTIMIZED SHIELD, TRIAXIAL CABLE	Date	2-25-13
		Revision	R
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
CONSTRUCTION DETAILS		ELECTRICAL CHARACTERISTICS	
DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED. 		CHARACTERISTIC IMPEDANCE 50 ± 2 ohms, Method A CAPACITANCE 27.0 pF/ft. (nominal) 30.0 pF/ft. (maximum) VELOCITY OF PROPAGATION 78% (nominal) ATTENUATION (maximum) 0.7 dB/100 ft. at 10 MHz 2.3 dB/100 ft. at 100 MHz 5.4 dB/100 ft. at 400 MHz 9.2 dB/100 ft. at 1000 MHz SURFACE TRANSFER IMPEDANCE 700 milliohms/meter (maximum) at .1 MHz - 1 GHz EMP RESPONSE (2ND SHIELD) 60.0 dB (minimum) for 1 meter	
CONDUCTOR AWG 12, 7 Strands of AWG 20, Silver-Coated Copper DIELECTRIC Rayfoam L Color - Natural 1ST SHIELD AWG 34, Silver-Coated Copper Water Sealant filling shield interstices WATERBLOCK LAYER Non-Woven Polyester 1ST JACKET Zerohal Color - Black 2ND SHIELD AWG 34, Silver-Coated Copper Optimized Water Sealant filling shield interstices WATERBLOCK LAYER Non-Woven Polyester 2ND JACKET Zerohal		ADDITIONAL REQUIREMENTS	
		ELECTRICAL CONDUCTOR RESISTANCE 1.9 ohms/1000 ft. (nominal) INSULATION RESISTANCE (DIELECTRIC) 10,000 megohms (minimum) for 1000 ft. JACKET FLAWS SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak) VOLTAGE WITHSTAND (DIELECTRIC) CONDUCTOR TO SHIELD 1500 volts (rms) (minimum) SHIELD TO SHIELD 500 volts (rms) (minimum)	
		ENVIRONMENTAL FLAMMABILITY Method B HEAT SHOCK 225°C LOW TEMPERATURE-COLD BEND -30°C/12.00 inch mandrel	
		PHYSICAL INSULATION (DIELECTRIC) ELONGATION 50% (minimum) TENSILE STRENGTH 1000 lbf/in ² (minimum) 2ND JACKET ELONGATION 150% (minimum) TENSILE STRENGTH 1200 lbf/in ² (minimum) 1ST SHIELD COVERAGE 90% (minimum) 2ND JACKET THICKNESS .043 inch (nominal) WRAP (EACH) .006 inch thick (nominal)	
Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 5012W5812-0) unless otherwise specified.		WEIGHT 147. lbs/1000 ft. (nominal)	
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.			
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
Page 1 of 1	Rayfoam, Zerohal, Cheminax, Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.		



Raychem Wire & Cable
 501 Oakeside Avenue
 Redwood City, California 94063-3800
 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

© 2005- 2013 Tyco Electronics Corporation, All rights reserved.