



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# 3M™ MicroTouch™ Display C1700SS

## The Clear Choice for Optics, Reliability, and Ease of Integration

The 3M MicroTouch Display C1700SS (17"), a robust metal chassis display using 3M's industry-standard surface capacitive touch technology, provides a durable, optically-enhanced, and cost competitive alternative to 5-wire resistive displays used in industrial automation equipment and kiosk enclosures. The C1700SS display offers multiple mounting options to make integration easy and a variety of bezel options for sealing against liquids and other contaminants.

### The Clear Choice

The C1700SS display utilizes an all-glass surface capacitive touch sensor with the proprietary 3M™ ClearTek™ Hard Coat to deliver superior durability, 91.5% light transmission, 225-nit brightness (with touch sensor), 500:1 contrast ratio and an ultra-fast 5.4 millisecond touch contact time.

### Multiple Mounting and Bezel Options

Multiple mounting and bezel options enable customers to meet their application needs at minimal cost. The C1700SS display offers a 75mm VESA pattern to provide arm mounting capability for industrial automation equipment. This minimizes the capital expenditure needed to upgrade equipment with touch. L-brackets are included for installations requiring the touch display to be fully enclosed.

The C1700SS display offers two bezel options. The Slimline bezel (optional) is flush with the edges of the display and is ideal for arm-mounted applications and is ideal for solutions that require a NEMA 1 seal rating. The Industrial Flanged bezel (optional), a metal-gasketed bezel, enables kiosks or others enclosures to support NEMA 4X / IP66 seal ratings.

### Cost Effective

The C1700SS display uses an all-glass touch sensor with no moving parts, whereas 5-wire resistive solutions rely on compressing the top film layer against a conductive coating to recognize touch. Since force is



required to activate a resistive touch sensor it is susceptible to mechanical wear and the appearance of "Newton Rings" which can potentially reduce product life and optical performance.

The C1700SS touch display operates reliably in the presence of on-screen contaminants and carries a 3-year "unlimited touches" warranty.

### Recommended Applications

- Industrial Automation
- Self Service
- Hospitality
- Security Systems
- Point-of-Information (POI)
- Home Automation

Feature	Benefit
All-Glass, One-Layer Solution	<ul style="list-style-type: none"> <li>• Provides 91.5% light transmission as compared to 80% for certain 5-wire resistive solutions</li> <li>• Unaffected by UV light that can cause degradation of optics and yellowing of film-based touch sensors over time</li> <li>• No moving parts improves reliability</li> <li>• Inherently free from the appearance of "Newton Rings"</li> </ul>
3M ClearTek Hard Coat	<ul style="list-style-type: none"> <li>• Proprietary coating is uniformly heat infused into the glass creating a non-permeable barrier for increased scratch and chemical resistance</li> <li>• Low surface energy coating promotes smooth finger drag</li> <li>• Unaffected by surface contaminants</li> </ul>
Total Touch Solution	<ul style="list-style-type: none"> <li>• Unlike other touch display manufacturers that utilize 3rd party touch sensors, electronics, and or software in their design, 3M owns, understands, and warranties the entire system for an unlimited amount of touches for 3 years</li> </ul>

# 3M™ MicroTouch™ Display C1700SS Specifications

## Functional Features

LCD Technology	TFT, Active Matrix
Display Colors	16.2 million
Pixel Pitch	.264mm
Brightness without touch sensor	250 cd/m <sup>2</sup> (nit) typical
Brightness with touch sensor (max.) <sup>1</sup>	225 cd/m <sup>2</sup> (nit) typical
Contrast Ratio	1000:1 typical
Video Response Time	5 ms typical
Touch Response Time	5.4 ms typical
Viewing Angle <sup>2</sup>	Horizontal: +/-80 degrees typical Vertical: +/-80 degrees typical
Control Type	OSD
On Screen Display Controls	Standard rear mounted controls.
Maximum Resolution	1280 x 1024
Operating Environment	0 to +40 degrees C Relative Humidity, non-condensing 90%
Storage Environment	-25 to +60 degrees C




With optional Slimline Bezel  
(Part Number: 2709122)



Optional Industrial Flange Bezel  
(Part Number: 5021104)

## Physical Features

Physical Dimensions (Enclosure) (WxHxD)	405.7 x 335.1 x 49 mm 15.98 x 13.18 x 1.93 inches
Display Area (WxH)	337.9 x 270.3 mm 13.3 x 10.6 inches
Video Cable Connector	15 Pin D-Sub
Power Supply Internal	12V DC Power Supply
Power Savings	DPMS, VESA Compliant
Power Consumption	30 watts normal operation
Backlight Life	50,000 hrs. typical
Weight	4.6kg/10.1 lbs
RoHS Compliant	Yes
Agency Approvals	FCC B, CE, UL/cUL
Mounting Options	Set of 2, side or top/bottom mounting brackets, VESA 75 mm
Warranty	3 years of unlimited touches



Mounting L-brackets (standard)

## Standard Part Numbers

Part Number	Description
11-4945-227-00	Serial (no bezel)
11-4945-225-00	USB (no bezel)

(1) Brightness measured on a display with 3M™ MicroTouch™ Sensor SCT3250 surface capacitive sensor.

(2) Measured at a contrast ratio of 10.

NOTE: Mechanical Drawings available at [www.3m.com/touch](http://www.3m.com/touch)

### 3M Touch Systems

Subsidiary of 3M Company  
501 Griffin Brook Park Drive  
Methuen, MA 01844  
U.S.A.

1-888-659-1080

[www.3m.com/touch](http://www.3m.com/touch)

**RoHS Directive compliant:** In accordance with European Directive 2002/95/EC, "RoHS Directive compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M. (9/06)

**IMPORTANT NOTICE TO PURCHASER:** Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. 3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. 3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)

