



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING			5021F1031
<b>CHEMINAX</b>	50 OHM, AWG 21, 19 STRANDS OF AWG 33, COAXIAL CABLE	Date	7-10-08
		Revision	L
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
<b>CONSTRUCTION DETAILS</b>		<b>ELECTRICAL CHARACTERISTICS</b>	
DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.  		CHARACTERISTIC IMPEDANCE                      50 ± 2 ohms, Method A CAPACITANCE    30.7 pF/ft. (nominal) VELOCITY OF PROPAGATION                      66% (nominal)	
		<b>ADDITIONAL REQUIREMENTS</b>	
		<b><u>ELECTRICAL</u></b>	
		CONDUCTOR RESISTANCE                      11.7 ohms/1000 ft. (nominal)	
		INSULATION RESISTANCE                      10,000 megohms (minimum) for 1000 ft.	
		JACKET FLAWS	
		SPARK TEST    1.0 kV (rms)	
		IMPULSE TEST    6.0 kV (peak)	
		VOLTAGE WITHSTAND (DIELECTRIC)              1000 volts (rms) (minimum)	
		<b><u>ENVIRONMENTAL</u></b>	
		FLAMMABILITY    Method B	
		HEAT SHOCK    225°C	
		LOW TEMPERATURE-COLD BEND                      -55°C/5.50 inch mandrel	
		VOLTAGE WITHSTAND (Post Environmental)              1000 volts (rms), 1 minute	
		<b><u>PHYSICAL</u></b>	
		INSULATION (DIELECTRIC)	
		ELONGATION    200% (minimum)	
		TENSILE STRENGTH    1800 lbf/in <sup>2</sup> (minimum)	
		JACKET	
		ELONGATION    200% (minimum)	
		TENSILE STRENGTH    2000 lbf/in <sup>2</sup> (minimum)	
		JACKET THICKNESS    .030 inch (nominal)	
		SHIELD COVERAGE    90% (minimum)	
		WEIGHT    29.7 lbs/1000 ft. (nominal)	
Outer jacket color will be translucent white (designated by a "-9X" appended to the part number, e.g. 5021F1031-9X) unless otherwise specified.			
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.			
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
The TE logo, Tyco Electronics, Cheminax, Raychem, and Rayolin are trademarks.			



**Raychem Wire & Cable**  
 501 Oakside Avenue  
 Redwood City, California 94063-3800  
 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.