



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION DETAILS	ELECTRICAL CHARACTERISTICS
<p>DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.</p> <p><b>CONDUCTOR</b> AWG 26, 19 Strands of AWG 38, Silver-Coated High Strength Copper Alloy</p> <p><b>DIELECTRIC</b> Rayfoam L Color - Natural</p> <p><b>1ST SHIELD</b> AWG 38 Silver-Coated Copper</p> <p><b>1ST JACKET</b> Thermorad® S Color - Black</p> <p><b>2ND SHIELD</b> AWG 38 Silver-Coated Copper</p> <p><b>2ND JACKET</b> Thermorad® S</p> <p>Outer jacket color will be black (designated by a "-0" appended to the part number, e.g., 5026D5314-0) unless otherwise specified.</p> <p>Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.</p>	<p><b>CHARACTERISTIC IMPEDANCE</b> 50 ± 2 ohms, Method A</p> <p><b>CAPACITANCE</b> 25.7 pF/ft. (nominal) 29.0 pF/ft. (maximum)</p> <p><b>VELOCITY OF PROPAGATION</b> 77% (nominal)</p> <p><b>ATTENUATION</b> 21.0 dB/100 ft. (maximum) at 400 MHz</p> <hr/> <p><b>ADDITIONAL REQUIREMENTS</b></p> <p><u><b>ELECTRICAL</b></u></p> <p><b>CONDUCTOR RESISTANCE</b> 42.0 ohms/1000ft. (nominal)</p> <p><b>INSULATION RESISTANCE</b> 10,000 megohms (minimum) for 1000 ft.</p> <p><b>JACKET FLAWS</b></p> <p>SPARK TEST 1.0 kV (rms)</p> <p>IMPULSE TEST 6.0 kV, (peak)</p> <p><b>VOLTAGE WITHSTAND (DIELECTRIC)</b></p> <p>CONDUCTOR TO SHIELD 1000 volts (minimum)</p> <p>SHIELD TO SHIELD 500 volts (minimum)</p> <p><u><b>ENVIRONMENTAL</b></u></p> <p><b>FLAMMABILITY</b> Method C</p> <p><b>HEAT SHOCK</b> 225°C</p> <p><b>LOW TEMPERATURE- COLD BEND</b> -55°C/3.50 inch mandrel</p> <p><b>VOLTAGE WITHSTAND (POST ENVIRONMENTAL)</b> 1000 volts (rms), 1 minute</p> <p><u><b>PHYSICAL</b></u></p> <p><b>INSULATION (DIELECTRIC)</b></p> <p>ELONGATION 50% (minimum)</p> <p>TENSILE STRENGTH 800 lbf/in<sup>2</sup> (minimum)</p> <p><b>JACKET (EACH)</b></p> <p>ELONGATION 200% (minimum)</p> <p>TENSILE STRENGTH 2000 lbf/in<sup>2</sup> (minimum)</p> <p>JACKET THICKNESS (EACH) .012 inch (nominal)</p> <p>SHIELD COVERAGE (EACH) 90% (minimum)</p> <p><b>WEIGHT</b> 14.0 lbs/1000 ft. (nominal)</p>

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.