



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## ZB10/WH-100:UNBEDRUCKT

Order No.: 5060883

The illustration shows versions ZB 10 - UNPRINTED, -LGS:CONSEC.NOS, -  
QR:CONSEC.NOS and -SO/CMS<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=5060883>

Zack strip, unprinted: 10-section, for individual labeling with M-PEN,  
ZB-T or CMS system, large batch, sufficient for labeling 1000 terminal  
blocks, for a terminal width of 10.2 mm, color: White

### Commercial data

EAN	4017918096113
Pack	100 pcs.
Customs tariff	39269097
Weight/Piece	0.002242 KG
Catalog page information	Page 489 (CL-2009)

### Product notes

WEEE/RoHS-compliant since:  
01/01/2005

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

Color	white
Inflammability class acc. to UL 94	V2
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Ambient temperature (operation)	-40 °C ... 100 °C

Components	free from silicone and halogen
Pitch	10 mm
Material	PA
Pitch	10 mm

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;