



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# 5075 Static Dissipative Wastebasket

**Clean and in control:  
Toss trash without tribogeneration**

The 5075 Static Dissipative Wastebasket is ideal for clean rooms, manufacturing, inspection, quality control and research industries where static control is crucial. This sturdy, high-density polyethylene container dissipates static electricity and does not tribogenerate. It contains no carbon, dyes, or additives that slough or outgas, making it suitable for all applications demanding cleanliness.

The surface resistivity of the wastebasket measures  $10^8$  -  $10^{11}$  ohms per square. The electrical properties are under warranty for one year from the date of purchase.

Roomy polyethylene anti-static trash can liners are available in pink and black. The average surface resistivity of the liners is  $10^{10}$  ohms per square. Static decay rate is less than two seconds per Mil-B-81705B Type II-Federal test method 101C method 4046.









## Easy to Maintain:

Clean with #6001 Mat & Table Top Cleaner to protect electrical properties. Use #2003 General Purpose Staticide for added protection.

**Product# 5075** Gray only  
11-gallon can (5 per case)

**Product #5076** Pink liner  
24" x 34" (50 per bundle)

**Product #5076B** Black liner  
24" x 34" (50 per bundle)

-  **Linear high-density polyethylene**
-  **13" diameter rim x 21.75" high**
-  **11-gallon container**
-  **Will not tribogenerate**
-  **Will not outgas**
-  **Accepts conductive bags and anti-static bags**
-  **No carbon or dyes**
-  **No silicone or plasticizers**

