## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



CASE FINISH	CURRENT (AMPS)	WORKING VOLTAGE				MAXIMUM	MAXIMUM		MINIMUM	MIN. INSERTION LOSS PER MIL-STD-220,										
		-55°C TO +85°C		-55°C TO +125°C		DC RESISTANCE (OHMS)	VOLTAGE DROP			30 1	00 1	150 20		FULL LOAD, +25°C   300 500 1 2 5 10   KHz KHz MHz MHz MHz MHz				10 100	100 1	
		AC	DC	AC	DC		DC	AC	(uF)						MHz	MHZM	IHz N	1Hz MHz	GHz	GH:
SOLDER	10		80		50	0.008	0.080		1.4	15		28 -	- 34	4	44		6	60	70	
M15733	IARKING: / 38-0004 2 DATE CC	DE																		
M15733 0LSP2 [	<u>Ge Markin</u> / 38-0004 DATE COD DC 10A 12 D21	E 5°C	50 x .070 SL [1.27 x 1. (2 PLC	77] — CS)	.370 [9.40] MAX.	0.1 Ø.1 [Ø2. (2 PL	10 <del>-</del>	AD Ø.375 [Ø9.52]	- .312 7.9 .302 7.6	92 <b>]</b> -		Ø	407 397 <b>[</b>	Ø10.3	33 <b>]</b> -	2212	20102			
<u>Markin</u> N/A	IG NOTES:		.16 .18	.150 [3.81] 0 [4.06] MIN 0 [4.57] MAX			1 5		.200 [5.08]		.095 .085	<u>5</u> 2.4 2.1 <u>М</u>	-					.68 .58]- <del>-</del>		
	<u>HEMATIC</u>	0					\$	2) TH CHA REC	<u>S:</u> DUNTING TOR IS PART COD NGE AUTHOR UIRED BEFO I BE MADE.	ED "N RITY.	NCA' CUS	". SCI STOM	DOE ER A	S NO	H TA	AVE L	S			
								CN 32381-CPD 52 CN 182252 51 CN 181539 50	DIMENSIC DIMENSIC IN INC N [ MILLIMI BY DO NOT	IFIED ONS AR CHES ETERS SCALE		TOLERANG DTHERWIS Decxx ± Decxxx Angles ± CODE I 0L	SE SPECI : .x <u>+</u> .xx <u>+</u> .010 0° 3	FIED [.25] Dv 10" Da NO. En	vn. Ha ate 9- igr. B.	CONTROL IN ASSETT 9-11 DEVINE of 1	Descript	PENNS	PASS _TER	NIA

Quality Products From The Specialists In Electro-Magnetic Compatibility