



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
G	01	P9		REVISED PER ECR-12-019888	17NOV12	KH	KR

SUGGESTED MATING TAB

SHOULDER MAY BE ELIMINATED IF NOT FEASIBLE

1 - MATL: 1/2H BRASS OR NICKEL PL STEEL.

2 - NO BURRS PERMISSIBLE AT HOLE.

3 - MUST BE FLAT WITHIN 0.076 [0.003] OVER THIS LENGTH.

4 - TIN PLATING IS REQUIRED ON BRASS WHEN TERMINAL TEMP. IS OVER 225°F

5 - HOLE MUST BE SYMMETRICAL ABOUT TAB Q WITHIN 0.076 [0.003]
* TO BE USED ONLY WHEN SHOULDER IS ELIMINATED.

1 FOR USE WITH MKII POSITIVE LOCK, LOW INSERTION FORCE FASTON RECEPTACLES AND MOST BUDGET FASTON RECEPTACLES.

2 PRELIMINARY - NOT FOR PRODUCTION

3 PREPRODUCTION - FASR REQUIRED

4 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

5 HOUSING MATERIAL MEETS MINIMUM GLOW WIRE FLAMMABILITY INDEX OF 850°C PER IEC 60695-2-12 AND MINIMUM GLOW WIRE IGNITION TEMPERATURE OF 775°C PER IEC 60695-2-13.

	66 NYLON V0, NATURAL	5	2-520935-3	2
	6 NYLON V2 RED		2-520935-2	
	6 NYLON V2 NATURAL	3	2-520935-1	
4	OBSOLETE V0 GREEN		1-520935-9	
4	OBSOLETE V0 BLACK	3	1-520935-8	
	V0 BROWN	2	1-520935-7	
4	OBSOLETE V0 YELLOW	3	1-520935-6	
	V0 BLUE		1-520935-5	
	V0 RED		1-520935-2	
	V0 NATURAL		1-520935-1	
	BLACK	2	520935-8	
	BROWN		520935-7	
	YELLOW		520935-6	
	BLUE		520935-5	
	GREEN		520935-4	
	WEATHER RESIST BLACK		520935-3	
	RED		520935-2	
	NATURAL		520935-1	
	COLOR		PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	4/14/88
DIMENSIONS: INCHES		CHK	M FEHER	4/14/88
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	R KUZO	4/14/88
0 PLC	± -	PRODUCT SPEC		
1 PLC	± -	APPLICATION SPEC		
2 PLC	± -			
3 PLC	± .010			
4 PLC	± -			
ANGLES	± -			
MATERIAL	FINISH	WEIGHT		
6/6 NYLON	SEE TABLE			
CUSTOMER DRAWING		SCALE	4:1	SHEET 1 of 1
		REV	P9	

HOUSING, RECPT, POSITIVE-LOCK & STANDARD FASTON, .250 SERIES, MKII

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C=520935	-

1471-9 (3/11)