



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



| Rev. | Rev. Date | Modified By | Brief Description |
|------|-----------|-------------|-------------------|
| | | | |

| Item | Unit | Specification |
|------------------|---|----------------------|
| Awg | Awg | 16# |
| No. of conductor | p,c | 4C |
| Conductor | Material | Stranded Bare Copper |
| | Filler | ---- |
| | Construction | No./mm 65/0.16BS |
| | Stranded diameter | mm 1.29 |
| Insulation | Material | CL2 PVC |
| | Nom. Thickness | mm 0.51(Ref.) |
| | Diameter | mm 2.3 ± 0.1 |
| | Color | red ,black |
| Filler | Material | 420D NYLON |
| Jacket | Material | CL2 PVC |
| | Min. Thickness | mm 0.85mm |
| | Nom. Thickness | mm 0.9(Ref.) |
| | O.D | mm 7.3 ± 0.2 |
| | Color | ---- |
| Marking | E326425 (UL) CL2 AUDIO CABLE 16AWG*4 STRANDED | |

Configuration:



CnC Tech, LLC

| | | | | | | |
|-------------------|-------|----------------------|----------------------|-------|--------|--------|
| GENERAL TOLERANCE | | APPROVED BY & DATE : | DESCRIPTION : | | | |
| 0-6 | ±0.05 | CHECKED BY & DATE : | 4-core in-wall 16AWG | | | |
| 6-18 | ±0.07 | | ITEM NO. : | | | |
| 18-50 | ±0.10 | DESIGNED BY & DATE : | DATE : | REV : | UNIT : | SHEET: |
| 50-120 | ±0.15 | | 2017/01/10 | A01 | MM | 1 OF 2 |

| NO. | PART NAME | SPECIFICATION DESCRIPTION | QTY | UNIT |
|-----|-----------|---------------------------|-----|------|
| ③ | | | | |
| ② | | | | |
| ① | | | | |