



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	16	c	REVISED PER ECO-10-004980	06MAY10	HMR FB

Technical drawing showing front and side views of a component. Dimensions include: 14.76±0.20 [.581±.008], 15.88±0.25 [.625±.010] MOUNTING HEIGHT, 8.59±0.38 [.338±.015], 0.64±0.20 [.025±.008] TYP, 3.48±0.25 [.137±.010], 4.11±0.43 [.162±.017], 7.37±0.51 [.290±.020], 0.63 [.025] TYP, 34.93±0.64 [1.375±.025], 21.21±0.51 [.835±.020], 8.76±0.25 [.345±.010], 11.07 MAX [.436], 1/2-28 UNEF-2A, 11.07 MAX [.436]. Callouts include CONTACT, DIELECTRIC, SHELL, HOUSING, MOUNTING PIN, CONTACT POST, and GROUND POST.

1 POLYESTER PBT PER MIL-M-24519, TYPE GPT-15F, UL94V-0 RATED, COLOR:NATURAL
 2 POLYMETHYLPENTENE, GENERAL PURPOSE.
 3 ZINC PER QQ-Z-363.
 4 BERYLLIUM COPPER PER QQ-C-530.
 5 BRASS PER ASTM-B-453.
 6 NICKEL PLATE PER QQ-N-290
 3.81 μm [.000150] MINIMUM THICK.
 7 TIN PLATE PER ASTM-B-545
 3.81 μm [.000150] MINIMUM THICK.
 8 GOLD PLATE PER MIL-G-45204
 .76 μm [.000030] MINIMUM THICK.
 9. SEE INSTRUCTION SHEET 408-2769.

RECOMMENDED PANEL CUTOUT
 Dimensions: 5.54 +0.08 / -0.00, .218 +.003 / -.000, 12.83 +0.13 / -0.00 DIA, .505 +.005 / -.000

PCB CONFIGURATION
 Dimensions: 2.01±0.08 DIA [.079±.003] 2 HOLES, 0.89±0.08 DIA [.035±.003] 2 HOLES, 10.16±0.08 [.400±.003], 5.09 [.200], 2.54 [.100], 5.08 [.200]

5414459-1
 PART NUMBER

RECOMMENDED PANEL CUTOUT

PCB CONFIGURATION

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. VARELA - DOCK5 20APR2005	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK J. HAVENER 20APR2005	NAME JACK, RIGHT ANGLE, PCB, 75 OHM, BNC	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± 0.05 [.002] 3 PLC ± - 4 PLC ± - ANGLES ± -		APVD S. BURKHOLDER 20APR2005	PRODUCT SPEC APPLICATION SPEC	
MATERIAL SEE NOTES 1 - 5		FINISH SEE NOTES 6 - 8	SIZE A2	CAGE CODE 00779
CUSTOMER DRAWING		WEIGHT -	DRAWING NO C=5414459	RESTRICTED TO -
		SCALE 90:1	SHEET 1 of 1	REV C

1471-9 (1/08)