



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




CONFIDENTIAL & PROPRIETARY


THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO LAIRD TECHNOLOGIES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN LAIRD TECHNOLOGIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM LAIRD TECHNOLOGIES.



GASKET ORIENTATION



GASKET SECTION "A-A"
NOT TO SCALE



SHEET DETAIL

NOTES:

1. MATERIAL: NICKEL/COPPER CONDUCTIVE FOAM WITH CONDUCTIVE ADHESIVE BACKING
2. GASKET DETAIL SHOWN ADHESIVE SIDE UP, ADHESIVE MAY BE OMITTED FOR CLARITY
3. THIS PART IS RoHS COMPLIANT

REVISIONS:

TITLE: SHIELDING GASKET	
Dwg. or Part No. 5418-KA-G1W	REV. 0

DRAWN D.D.G.	DATE 9/10/03	SCALE: 1/1
CHECKED BY: PER	DATE 9/15/03	
RELEASED BY: PER	DATE 9/15/03	

DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS:		
DECIMALS	LENGTH	
.XX ± .03	0" - 6"	± .030"
.XXX ± .020	6" - 11"	± .050"
	11" - 48"	± .100"
ANGLES	48° - 70°	± .187°
	± 1/2°	70° - 144° ± .250°

