



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: 553-50002



Heat Shrink Labels, Single Side, Unslit, .125" (3.17mm), PO-X, White, 250/box

Article Number	553-50002
Type	HST3-1WH
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">• Slide Slit and optional center slits for easy wire insertion.• Smooth surface for clean and legible printing.• Supplied on a ladder style carrier so that markers can be kitted after printing.• A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description	Heat Shrink Labels, Single Side, Unslit, .125" (3.17mm), PO-X, White, 250/box
Global Part Name	HST3-1WH-PO-X-WH
Variant	Thin-Wall
Width W (Imperial)	1.9
Width W (Metric)	48.26
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	0.235
Height H (Metric)	5.69
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.125
Outside Diameter OD(metric)	3.2
Outside Diameter Max(Imperial)	0.125
Outside Diameter Max (metric)	3.2
Wall Thickness WT (Imperial)	0.0209
Wall Thickness WT (Metric)	0.53

Material	Polyolefin, cross-linked (PO-X)
-----------------	---------------------------------

Material Shortcut PO-X

US MIL SPEC	MIL-STD-202G Method 215K
--------------------	--------------------------

SAE-AS81531

AMS-DTL-23053/5 Class 1 and 3

Flammability

UL 224 VW-1

Halogen free

No

Operating Temperature (Metric)

-67°F to +275°F (-55°C to +135°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

UL 224 125 °C 600V VW-1

Package Quantity(Imperial)	250
-----------------------------------	-----

Package Quantity (Metric) 250

Customs Number	3926909987
-----------------------	------------

Content Unit(BMEcat) pack

Weight (Metric)	0.294
------------------------	-------

Weight (Imperial)

0.64

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)