mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HellermannTyton

Specification Sheet

Part Number: 553-50192



Heat Shrink Labels, Single Side, Unslit, .38" (9.52mm), PO-X, White, 1000/box

Article Number	553-50192
Туре	HST9-3WH
Color	White (WH)
Features & Benefits	• Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
Quantity Per	box
Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description

Global Part Name

HST9-3WH-PO-X-WH

Variant	Thin-Wall
Width W (Imperial)	1.9
Width W (Metric)	48.26
Thickness T (Imperial)	.003
Thickness T (Metric)	.0762
Height H (Imperial)	0.597
Height H (Metric)	15.16
Width of Liner (Metric)	76.2
Width of Liner (imperial)	3.0
Outside Diameter OD(Imperial)	0.375
Outside Diameter OD(metric)	9.52
Outside Diameter Max(Imperial)	0.375
Outside Diameter Max (metric)	9.52
Wall Thickness WT (Imperial)	0.031
Wall Thickness WT (Metric)	0.79

Material	Polyolefin, cross-linked (PO-X)	
Material Shortcut	PO-X		
US MIL SPEC	SAE-AS81531		
MIL-STD-202G Method 215K AMS-DTL-23053/5 Class 1 and 3 Flammability			
UL 224 VW-1		Halogen free	
No		Operating Temperature (Metric)	
-67°F to +275°F (-55°C to +135°C)		Reach Complaint(Article 33)	
Yes		ROHS Complaint	
Yes		Certification/Specification WEB	
SAE - AMS - DTL-23053/5 Class 1 and 3 SAE - AS81531 UL 224 125 °C 600V VW-1			
Package Quantity(Imperial)	1000		
Package Quantity (Metric)	1000		
Customs Number	3926909987		
Content Unit(BMEcat)	pack		

Labels per Column	1
Labels per Row	1
Weight (Metric)	1.72
Weight (Imperial)	3.72

© 2018 HellermannTyton. All rights reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions