

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## **HellermannTyton**

## **Specification Sheet**

Part Number: 558-00056

## HellermannTyton

SwiftMark Self-Laminating Label, 1.5" x 1.0" x 3.0", VL, White, 1000/roll

Article Number	558-00056
Туре	TAG85-100W381SM
Color	White (WH)
Features & Benefits	<ul> <li>HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.</li> <li>Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li> <li>Labels are UL recognized for indoor and outdoor use to expand application options.</li> <li>HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.</li> </ul>
Quantity Per	roll

<b>Product</b>	Doccri	ntion
Product	Descri	puon

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Short Description	SwiftMark Self-Laminating Label, 1.5" x 1.0" x 3.0", VL, White, 1000/roll
Global Part Name	TAG85-100W381SM-100B-WH
Technical Description	SwiftMark Self-Laminating Label, 1.5" X 1.0" X 3.0", White
Variant	Roller form
Width W (Imperial)	1.5
Width W (Metric)	38.1
Bundle Diameter Min (Imperial)	.14
Bundle Diameter Min (Metric)	3.50
Bundle Diameter Max (Imperial)	0.29
Bundle Diameter Max (Metric)	7.37
Thickness T (Metric)	35
Height H (Imperial)	0.5

Height H (Metric)	12.70
Width of Liner (Metric)	41.27
Width of Liner (imperial)	1.625
Outside Diameter Max(Imperial)	0.39
Outside Diameter Min (metric)	10.1
Outside Diameter Min(Imperial)	0.79
Outside Diameter Max (metric)	20.2
Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
Material  Material Shortcut	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating 100B
Material Shortcut	100B
Material Shortcut  Adhesive	100B Acrylic
Material Shortcut  Adhesive  Adhesive Operating Temperature	100B  Acrylic  -40°F to +194°F (-40°C to +90°C)
Material Shortcut  Adhesive  Adhesive Operating Temperature  Operating Temperature (Metric)	100B  Acrylic  -40°F to +194°F (-40°C to +90°C)  -40°F to +176°F (-40°C to +80°C)

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Row	1
Weight (Metric)	0.94
Weight (Imperial)	2.08

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

<sup>© 2018</sup> HellermannTyton. All rights reserved.