



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Specification Sheet

Part Number: 558-00059



SwiftMark Self-Laminating Label, 2.0" x 1.5" x 3.75", VL, White, 1000/roll

Article Number	558-00059
Type	TAG111-190W508SM
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">• HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.• Labels are UL recognized for indoor and outdoor use to expand application options.• HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.
Quantity Per	roll

Product Description	<p>HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).</p>		
Short Description	SwiftMark Self-Laminating Label, 2.0" x 1.5" x 3.75", VL, White, 1000/roll		
Global Part Name	TAG111-190W508SM-100B-WH		
Technical Description	SwiftMark Self-Laminating Label, 2.0" X 1.5" X 3.75", White		
Variant	Roller form		
Width W (Imperial)	2.0		
Width W (Metric)	50.8		
Bundle Diameter Min (Imperial)	.06		
Bundle Diameter Min (Metric)	1.50		
Bundle Diameter Max (Imperial)	0.12		
Bundle Diameter Max (Metric)	3.0		
Thickness T (Metric)	25		
Height H (Imperial)	0.35		

Height H (Metric)	8.89
Width of Liner (Metric)	53.97
Width of Liner (imperial)	2.125
Outside Diameter Max(Imperial)	0.87
Outside Diameter Min (metric)	10
Outside Diameter Min(Imperial)	0.393
Outside Diameter Max (metric)	22.2
Material	Type 100, Vinyl (PVC), white (WH), self laminating
Material Shortcut	100B
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Operating Temperature (Metric)	-40°F to +176°F (-40°C to +80°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL-Recognized
UL Recognized (US)	Yes

Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Row	1
Weight (Metric)	1.41
Weight (Imperial)	3.10