



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# SPECIFICATION CONTROL DRAWING


**55A1151**

Title FIVE CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, 600 VOLT

Date 10-12-05

Revision B

This specification sheet forms a part of the latest issue of Raychem Specification 55A.



| CABLE CONSTRUCTION DETAILS |                         |                      |                           |         |                           |         |                                |
|----------------------------|-------------------------|----------------------|---------------------------|---------|---------------------------|---------|--------------------------------|
| PART NUMBER<br>1/          | CONDUCTOR SIZE<br>(AWG) | SHIELD SIZE<br>(AWG) | JACKET THICKNESS<br>(in.) |         | OUTSIDE DIAMETER<br>(in.) |         | MAXIMUM WEIGHT<br>(lb/1000 ft) |
|                            |                         |                      | MINIMUM                   | NOMINAL | NOMINAL                   | MAXIMUM |                                |
| 55A1151-30-*               | 30                      | 38                   | .006                      | .008    | .098                      | .111    | 9.0                            |
| 55A1151-28-*               | 28                      | 38                   | .006                      | .008    | .106                      | .120    | 10.8                           |
| 55A1151-26-*               | 26                      | 38                   | .006                      | .008    | .119                      | .135    | 14.3                           |
| 55A1151-24-*               | 24                      | 38                   | .006                      | .008    | .133                      | .151    | 18.4                           |
| 55A1151-22-*               | 22                      | 38                   | .006                      | .008    | .149                      | .170    | 24.1                           |
| 55A1151-20-*               | 20                      | 38                   | .006                      | .008    | .171                      | .193    | 33.5                           |
| 55A1151-18-*               | 18                      | 38                   | .006                      | .008    | .198                      | .224    | 47.4                           |
| 55A1151-16-*               | 16                      | 38                   | .007                      | .009    | .221                      | .250    | 58.6                           |
| 55A1151-14-*               | 14                      | 38                   | .007                      | .009    | .267                      | .305    | 85.8                           |
| 55A1151-12-*               | 12                      | 38                   | .007                      | .009    | .316                      | .364    | 124.                           |
| 55A1151-10-*               | 10                      | 36                   | .008                      | .010    | .387                      | .446    | 197.                           |

### CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C  
 Maximum continuous conductor temperature  
 VOLTAGE RATING: 600 volts (rms) at sea level  
 ACCELERATED AGING: 300 ± 3°C for 7 hours  
 BLOCKING: 200 ± 3°C for 6 hours  
 DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz  
 FLAMMABILITY: Procedure 1,  
 3 seconds (maximum); 3 inches (maximum);  
 no flaming of facial tissue  
 JACKET COLOR: White preferred  
 JACKET ELONGATION AND TENSILE STRENGTH:  
 Elongation, 50% (minimum)  
 Tensile Strength, 5000 lbf/in<sup>2</sup> (minimum)  
 JACKET FLAWS:  
 Spark Test, 1000 volts (rms)  
 Impulse Dielectric Test, 6.0 kV (peak)

LIFE CYCLE: 200 ± 3°C for 168 hours  
 LOW TEMPERATURE-COLD BEND: -65 ± 2°C for 4 hours  
 SHIELD COVERAGE: 85% (minimum)  
 VOLTAGE WITHSTAND TEST (Post Environmental):  
 1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:  
 The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.  
 1/ Example: AWG 22, black, brown, red, orange and yellow component wires; white jacket:  
 55A1151-22-0/1/2/3/4-9

NOTE: Nominal values are for information only.  
 Nominal values are not requirements.

*Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.*

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx") OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



**Raychem Wire & Cable**  
 501 Oakside Avenue  
 Redwood City, CA 94063-3800  
 Phone: 1-800-227-8816  
 Fax: 1-650-361-6297