



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




ASSY. NO. (CAT. NO.)	LED COLOR	
	POSITION 1	POSITION 2
567-0101F	BLANK	RED
567-0102F	BLANK	GREEN
567-0103F	BLANK	YELLOW
567-0111F	RED	RED
567-0112F	RED	GREEN
567-0113F	RED	YELLOW
567-0121F	GREEN	RED
567-0122F	GREEN	GREEN
567-0123F	GREEN	YELLOW
567-0131F	YELLOW	RED
567-0132F	YELLOW	GREEN
567-0133F	YELLOW	YELLOW

OPERATING CHARACTERISTICS AT T_A = 25 °C

SYMBOL	PARAMETER	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
V _F	FORWARD VOLTAGE	RED		2.1	2.8	V	I _F = 20 mA
		YELLOW		2.1	2.8		
		GREEN		2.1	2.8		
V _R	REVERSE CURRENT	ALL			100	μA	V _R = 5 V
λ _d	DOMINANT WAVELENGTH	RED	635			nm	SEE NOTE 1
		YELLOW	583		589		
		GREEN	562		568		
I _V	LUMINOUS INTENSITY	RED	1.1	3.7		mcd	I _F = 10 mA
		YELLOW	2.2		6.4		
		GREEN	2.2		6.4		

REV	ECN NO	REVISIONS	DRN	CKD	APP	DATE
A		NEW RELEASE	CE	NO	MES	4-3-07
B		ADDED P/N 567-0131F	AJF	KLJ	NO	8-3-09

RoHS Compliant 567-01XXF
 Part Numbers with the "F" suffix ending are RoHS Compliant.
 Example: 567-0122F
 Packaging is marked with "RoHS Compliant" label or equivalent markings.
 Parts can be wave soldered, dip soldered or hand soldered using typical lead-free soldering process with max 260°C temp. for 5 sec.



NOTES

- MEASURED WITH EXELTRON MODEL 2001.
- PIN NUMBERS FOR REFERENCE ONLY, DESIGNATION NON-EXISTENT ON PART.
- DIALIGHT PART NUMBER: 567-0101F THRU 567-0133F (SEE CHART FOR ALL P/N)
- THIS ASSEMBLY CONTAINS ELECTROSTATIC DISCHARGE SENSITIVE DEVICES (ESDS). MAINTAIN ALL PRECAUTIONARY MEASURES DURING ASSEMBLY, HANDLING AND STORAGE IN ACCORDANCE WITH IPC-A-610.



ATTENTION:
 OBSERVE PRECAUTIONS FOR
 HANDLING ELECTROSTATIC
 SENSITIVE DEVICES

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE: DRAWING SCALE ALL DIM'S IN: INCHES (MM)	DRAWING NUMBER C-17481	REV B
TOLERANCES: UNLESS OTHERWISE SPECIFIED FRACTIONS: ±1/64 DECIMALS (.XX): ±.01 DECIMALS (.XXX): ±.005 DECIMALS (.XXXX): ±.0005 ANGLES: ±1°	TITLE 2mm x 4mm RECT. LED CBI RoHS COMPLIANT	
FINISH:	MATERIAL	
FSCM 83330	Dialight 1501 ROUTE 34 SOUTH FARMINGDALE, NJ 07727	
SHEET 1 OF 1		FAMILY TABLE: