



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Specification Sheet

Part Number: 596-00816

VOLTAJE NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
FRECUENCIA NOMINAL DE OPERACIÓN DE CA	<input type="text"/>
POTENCIA MÁXIMA DE CA	<input type="text"/>
CORRIENTE MÁXIMA DE CA	<input type="text"/>
SOBRECORRIENTE NOMINAL MÁXIMA DEL DISPOSITIVO PARA PROTECCIÓN DEL MODULO DE CA	<input type="text"/>

### Article Number

596-00816

### Type

AC2011S

### Color

Red (RD)

### Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high-performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

### Quantity Per

roll

### Product Description

HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Short Description**

Solar Label, Printable, Spanish, AC MODULE, 4.0" x 2.0", PET, Red, 50/roll

**Global Part Name**

AC2011S-840/926-RD

**Technical Description**

Printable Solar Label, Spanish Version, AC MODULE LABEL, 4.0" X 2.0", Red

**Local Order Number 2**

English Version: 596-00252

**Length L (Imperial)**

4.0

**Length L (Metric)**

101.6

**Width W (Imperial)**

4.0

**Width W (Metric)**

101.6

**Height H (Imperial)**

2.0

**Height H (Metric)**

50.8

**Material**

Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

**Material Shortcut**

840/926

**Adhesive**

Acrylic

**Halogen free**

Yes

**Adhesive Operating Temperature**

-40°F to +180°F (-40°C to +82°C)

**Operating Temperature (Metric)** -40°F to +302°F (-40°C to +150°C)

**ROHS Complaint** Yes

**Certification/Specification WEB** CSA 66956

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 50

**Package Quantity (Metric)** 50

**Customs Number** 3919102055

**Labels per Column** 1

**Labels per Row** 1