mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





UHF RFID Inlays



direct attach

Dimensions:

Operating Frequency: Global (860 - 960MHz) RF Protocol: ISO-18000-6C, EPC Class 1 Gen 2 Chip: NXP UCODE G2iL EPC Memory: 128 bit TID Memory: 64 bit Tag IDentifier (TID) including 32 bit factory locked unique

866-903- RFID (7343) / rfid.info@averydennison.com



Common Applications:

- Apparel and Retail
- Jewelry

Part Number	600404	600405
Format	Dry Inlay	Wet (pressure- sensitive) Inlay
Antenna dimensions (CDxMD)	1.63 x 0.63 in [41.4 x 16 mm]	1.63 x 0.63 in [41.4 x 16 mm]
Die- cut dimensions	N/ A	1.75 x 0.75 in [44.45 x 19.05 mm]
Inlay substrate material	PET	PET
Inlay- to- liner adhesive	N/ A	S-490 (FASSON)
Liner material	N/ A	1.5M Clear PET
Face sheet	N/ A	N/ A
Standard pitch	1.5 in [38.1 mm]	1.5 in [38.1 mm]
Standard web width	2.0 in [50.8 mm]	2.0 in [50.8 mm]
Total thickness over chip	10 -13 mils [254 - 330.2 microns]	14 -17 mils [356 - 431.8 microns]
Operating temperature	-40 to 185 F [-40 to 85 C]	-40 to 185 F [-40 to 85 C]
RoHS	EU Directive 2011/65/ EU Compliant	EU Directive 2011/65/ EU Compliant
Quality assurance	Compliant 100% read tested with out- of tolerance inlay marked	Compliant 100% read tested with out- of tolerance inlay marked
Un- wind direction	Inlay - side Out	Inlay - side Out
Core size with adaptor insert	3 in [76.2mm]	3 in [76.2 mm]
Maximum roll outer diameter (not to exceed)	15.38in [390.65 mm]	13 in [330.2 mm]
Average # of units per roll	12,000	12,000
Rev	00	00

CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environmental static charge to a minimum.

APPLICATIONS This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

WARRANTY Please refer to Avery Dennison RFID standard terms and conditions. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

PRODUCT CHANGES Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice.

TRADEMARK STATEMENT Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit www.rfid.averydennison.com.

© 2014 Avery Dennison Inc. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342