



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





RFID

UHF RFID Inlays
AD-380iM



Dimensions	1.97 x 1.18 in (50 x 30mm)
Operating Frequency	Global (860 – 960 MHz)
RF Protocol	ISO-18000-6C, EPC Class 1, Gen 2
Chip	NXP UCODE G2iM
EPC Memory	256 bits plus 512 bits User Memory
TID Memory	96 bits with 48 bit unique serial number

Common Applications
 Supply Chain, Inventory and Logistics

Toll free US 866-903- RFID (7343) / rfid.info@averydennison.com
 International +1-770-965-0807

PART NUMBER	600612	600660
Format	Dry Inlay	PS Inlay
Antenna dimensions (CDxMD)	1.97 x 1.18 in (50 x 30mm)	1.97 x 1.18 in (50 x 30mm)
Die-cut dimensions	N/A	2.13 x 1.34 in (54 x 34mm)
Inlay substrate material	PET	PET
Inlay-to-liner adhesive	N/A	S-490 (FASSON)
Liner material	N/A	40# SCK
Face Sheet	N/A	N/A
Standard pitch	1.5 in (38.1mm)	1.5 in (38.1 mm)
Standard web width	2.126 in (54mm)	2.284 in (58 mm)
Total thickness over chip	9-10 mils (229 – 254 microns)	10-12 mils (254 – 305 microns)
Operating temperature	-40 to 185F (-40 to 85C)	-40 to 185F (-40 to 85C)
RoHS	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant
Quality assurance	100% read tested with out-of-tolerance inlay marked	100% read tested with out-of-tolerance inlay marked
Un-wind direction	Inlay-side Out	Inlay-side Out
Core size with adaptor insert	3 in (76.2mm)	3 in (76.2mm)
Maximum roll outer diameter (not to exceed)	13 in (330.2mm)	13 in (330.2mm)
Average # of units per roll	15,000 verified	10,000 verified
Rev	00	00

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

Warranty: Please refer to Avery Dennison RFID standard terms and conditions.

Product Information: Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

Trademark statement: Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit www.rfid.averydennison.com.