



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED
G		REVISED PER ECNR T-19555	9/5/79	M.HIGBY
H		REVISED PER DCR# T-22015	12/16/98	M.HIGBY

CONTACT CHARACTERISTICS:

- MATERIALS:
  - CONTACT BODY: BRASS, UNS ALLOY NO. C36000, TEMPER H02, SPEC ASTM B16.  
PLATING: GOLD PER ASTM B 498 (MIL-G-45204) OVER NICKEL PER QQ-N-290
  - RATAINING CLIP: BERYLLIUM COPPER, UNS ALLOY NO. C17200 TEMPER TH04, SPEC. ASTM B194.  
PLATING: NICKEL PER QQ-N-290.
  - SOLDER: SN83 RMAP IN ACCORDANCE WITH ANSMJ-STD-008.
  - CABLE SUPPORT TUBING: POLYVINYLIDENE HEAT SHRINKABLE TUBING.
- TEMPERATURE RATING: 125°C MAXIMUM
- MECHANICAL AND ELECTRICAL PERFORMANCE:  
THIS CONTACT IS QUALIFIED TO RAYCHEM SPECIFICATION D-6002.  
MIL-C-39029 TYPE "A" SIZE 16 REQUIREMENTS APPLY UNLESS OTHERWISE SPECIFIED IN D-6002.
- THIS CONTACT MATES WITH D-610-10, MS 17804-16-16, MS 17804-16-20, MS 17808-16-18 AND MS 17808-16-20.
- CONTACT REMOVAL TOOL: AD-1447.
- FOR TERMINATION PROCEDURE SEE ES 61187.
- D-610-09 IS DESIGNED TO ACCOMMODATE 16 AWG THRU 20 AWG TIN OR SILVER PLATED WIRE OF Ø .120 MAX. INSULATION. OTHER APPLICATION SHOULD BE SUBMITTED TO RAYCHEM FOR EVALUATION.

If this document is printed it becomes uncontrolled.  
Check for the latest revision.

DO NOT SCALE THIS DRAWING

**SPECIFICATION CONTROL DRAWING**

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES (BRACKETED DIMENSIONS ( ) ARE METRIC AND TOLERANCES ARE:  XXX: ± ( ) .XX: ± ( ) .Δ: ± ( )	DRAWN	B.OEASY	9-4-80	 <small>Raychem Corporation 200 West 104th Street New York, NY 10026 USA</small>	TITLE	
	CHECKED				CONTACT, MALE, SIZE 16	
	APPROVED	<i>BOS</i>	9-4-80			
	APPROVED	<i>HW</i>	9/4/80			
	CAD NAME	T22015.TIF	SIZE	CODE IDENT	DWG. NO.	
			A	NO. 06090	D-610-09	H
					WEIGHT	SHEET 1 OF 1