



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



VAC19KS, Europlug, V-Lock cord retaining, 2.0 m, Connector IEC C19, H05VV-F3G1.5, black



Description

- Power Cord ,
- Protection class I , Pin temperature 70 °C ,
- with V-Lock interlocking system

Technical Data

| | | | |
|---------------------------------|---|-------------------------|--|
| Ratings IEC | 16 A / 250 VAC; 50/60Hz | appliance inlet/-outlet | C19 acc. to IEC 60320-1 |
| Dielectric Strength | > 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50Hz) | | (for cold conditions) pin-temperature 70 °C, 16A, Protection Class I |
| Allowable Operation Temperature | -25 °C to 70 °C | | |
| IP-Protection | from front side IP 20 acc. to IEC 60529 | | |
| Insulation cover | Suitable for appliances with protection class I acc. to IEC 61140 | | |
| Terminal | moulded | | |
| Material: Housing | PVC, black | | |

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

All Variants

| Connector | | cable | | | | Plug | | | | | Order Number |
|-----------|--------|--------------|-------------------------|------------|-------|----------|---------|-------------|----------|-------|--------------|
| Type | V-Lock | Cord Type | Conductor cross section | Length [m] | Color | Type | Country | Standard | Style | Index | |
| C19 | ● | H05VV-F3G1.5 | 3 x 1.5 mm ² | 2.0 | black | Europlug | EU | CEE 7 / VII | straight | - | 6051.2043 |

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 40 Pcs

Mating Inlets/Plugs shuttered

Category / Description

[Appliance Inlet Overview complete](#)



| | |
|--|------|
| IEC Appliance Inlet C20 or C24, Split panel or screw-on mounting, PCB Terminal | GSP4 |
| IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal | 1601 |
| IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal | 4798 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal | 4793 |
| IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal | 1624 |
| Appliance Inlet further types to 6051.2043 | ... |

[IEC Inlet Filter Overview complete](#)



| | |
|---|------|
| IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting | 5130 |
| C20F, 20 A, prewired, Standard and Medical Version, Solder, quick connect or wires (stranded), Capacitor: X2, Screw, Mounting Front-/Rear-Side, Power Entry Modules with Filter | C20F |
| IEC Inlet Filter further types to 6051.2043 | |

[Power Entry Module Overview complete](#)



| | |
|---|------|
| IEC Appliance Inlet C20 with Line Switch, 2-pole | EC11 |
| 0 0 0 0 0 0 | 6136 |
| IEC Appliance Inlet C20 with Circuit Breaker TA45 | EF11 |

[Power Entry Module further types to 6051.2043](#)

[Power Entry Module with line filter Overview complete](#)



| | |
|--|------|
| EC12, 20 A, prewired, Standard and Medical Version, Quick connect terminals 6.3 x 0.8 mm, Capacitor: X2, Screw, Mounting Front-Side, Power Entry Modules with Filter | EC12 |
| IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed) | EF12 |

[Power Entry Module with line filter further types to 6051.2043](#)