

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







VAC19KS, Interconnection, V-Lock cord retaining, 2.0 m, Connector IEC C19, H05VV-F3G1.5, black

















Description

- Interconnection Cord
- Protection class I , Pin temperature 70 $^{\circ}\text{C}$
- with V-Lock interlocking system

Technical Data

Ratings IEC	16A / 250VAC; 50/60Hz
Dielectric Strength	> 2 kVDC between L-N
	> 2 kVAC between L/N-PE
	(1 min/50 Hz)
Allowable Operation Tempe-	-25 °C to 70 °C
rature	
IP-Protection	from front side IP 20 acc. to IEC 60529
Insulation cover	Suitable for appliances with protection
	class I acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black

appliance inlet/-outlet	C19 acc. to IEC 60320-1
	(for cold conditions) pin-temperature 70
	°C, 16A, Protection Class I

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in General Product Information

All Variants

Connector cable			Plug					Order Number			
Туре	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Туре	Country	Standard	Style	Index	
C19	•	H05VV- F3G1.5	3 x 1.5 mm ²	2.0	black	Interconnec-	INT	IEC 60320-1	straight	-	6051.2047

Most Popular.

Availability for all products can be searched real-time: http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 40 Pcs

Mating Inlets/Plugs shuttered

Category / Description



Appliance Inlet Overview complete

IEC Appliance Inlet C20 or C24, Split panel or screw-on mounting, PCB Terminal	GSP4
IEC Appliance Inlet C20, Screw-on Mounting, Rear Side, PCB Terminal	1601
IEC Appliance Inlet C20, Screw-on Mounting, Front Side, Solder or Quick-connect Terminal	4798
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick-connect Terminal	4793
IEC Appliance Inlet C20, Snap-in Mounting, Front Side, Solder or Quick Connect Terminal	1624
Appliance Inlet further types to 6051 2047	



IEC Inlet Filter Overview complete

IEC Appliance Inlet C20 with Filter, ECO design, front or rear side Mounting	5130
C20F, 20 A, prewired, Standard and Medical Version, Solder, quick connect or wires (stranded), Capacitor: X2, Screw, Mounting Front-/Rear-Side, Power Entry Modules with Filter	C20F



Power Entry Module Overview complete

IEC Inlet Filter further types to 6051.2047

IEC Appliance Inlet C20 with Line Switch, 2-pole	EC11
000000	6136
IEC Appliance Inlet C20 with Circuit Breaker TA45	EF11

Power Entry Module further types to 6051.2047



Power Entry Module with line filter Overview complete

EC12, 20 A, prewired, Standard and Medical Version, Quick connect terminals 6.3 x 0.8 mm, Capacitor: X2, Screw, Mounting Front-Side, Power Entry Modules with Filter	EC12
IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)	EF12
Power Entry Medula with line filter further types to 6051 2047	

Mating Outlets/Connectors shuttered



Appliance Outlet Overview complete

IEC Appliance Outlet J, Snap-in/Screw-on Mounting, Front Side, Solder or Quick-connect Terminal	4797	
IEC Appliance Outlet J, Snap-in Mounting, Front Side, IDC Terminal	4710	
Appliance Outlet further types to 6051.2047		