



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




DIALIGHT ASSEMBLY NO.	LED COLOR	OPERATING VOLTAGE
609-1122-120	RED	6 V
609-1222-120	GREEN	6 V
609-1322-120	YELLOW	6 V
609-1122-130	RED	12 V
609-1222-130	GREEN	12 V
609-1322-130	YELLOW	12 V
609-1122-140	RED	24 V
609-1222-140	GREEN	24 V
609-1322-140	YELLOW	24 V

NOTES:

1. MOUNTING HOLE SIZE:  $\phi$  9.3mm (.366)
2. MAXIMUM PANEL THICKNESS: 7.5mm (.295)
3. MATERIALS:
  - 3.1. METAL HOUSING: BRASS, CHROME PLATED WITH BLACK COATING;
  - 3.2. MOUNTING HEX NUT: BRASS, NICKEL PLATED;
  - 3.3. SPLIT LOCK WASHER: STEEL, NICKEL PLATED;
  - 3.4. HEADER/INSULATOR: POLYCARBONATE, COLOR: BLACK.
4. SOLDERABILITY: PER ANSI/JPC-S-805, METHOD A.
5. DIALIGHT PART NO. 609-1122-1X0 (SEE CHART ABOVE)

LED CHARACTERISTICS TABLE

COLOR	PEAK WAVE LENGTH $\lambda_p$ (nm)	RECOMMENDED OPERATING CURRENT (mA)	ABSOLUTE MAXIMUM RATINGS					ELECTRO-OPTICAL CHARACTERISTICS						
			$I_f$ (mA)	$I_{RM}$ (mA)	$I_{RPM}$ (mA)	$T_{op}$ ( $^{\circ}$ C)	$T_{stg}$ ( $^{\circ}$ C)	SR	$V_f$ (V)	$I_{fmax}$ (mA)	$I_{fmin}$ (mA)	BRIGHTNESS (Cand)		
RED	635	15	30	50	5	-25 to +85	-25 to +100	2.0	2.8	20	10	4	80	20
GREEN	565	15	30	50	5	-25 to +85	-25 to +100	2.1	2.8	20	10	4	150	20
YELLOW	585	15	30	50	5	-25 to +85	-25 to +100	2.0	2.8	20	10	4	120	20



REV	ECN NO.	REVISIONS	DEM. CND. APP.	DATE
A		NEW RELEASE	DC	9/8/3-15-06

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.

SCALE: NONE  
 ALL DIM'S. IN: INCHES  
 UNLESS OTHERWISE SPECIFIED  
 FUNCTIONS: d/144  
 REVISIONS: 1: 8/28  
 REVISIONS: 2: 8/15  
 FINISH: #3

DRAWING NUMBER: C-16671  
 TITLE: 9mm LED PH1  
 MATERIAL: A

FSCN 83330  
 SHEET of FAMILY TABLE:

Dialight  
 1913 ATLANTIC AVE.  
 MANASSAS, N.J. 08735