## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Copyright FCI.	2 FCIconnect.co	r 3	4
14.41 R0.25 MAX. TYP.		PRODUCT NO NUMBER LOADED HSG OF POS. POSITION COLOR	PLATING
9.28 9.29 15.63		61885-0661         ALL POS.           61885-0641         2,3,4,5           61885-0661LF         3,4           61885-0641LF         2,3,4,5           61885-0641LF         2,3,4,5           61885-0621LF         3,4	5u" Au + high performance lubricant
RECOMMENDED PANEL CUT-OUT	Immended panel cut-out     Immended panel cut-out		
$\underbrace{0.89}^{5.08}$	0 0 0 0 0 0 0 0	<ul> <li>2. HOUSING MAT'L: N C</li> <li>3. CONTACTS: PHOS Ø 0.460</li> <li>4) METAL SHELL MATI COPPER ALLOY, O FINISH: FOR 6188 FOR 6188</li> <li>5. PACKAGING PER G</li> <li>6. IF LF P/N THE PR DIRECTIVES AND O DESCRIBED INS GS</li> <li>7. IF LF P/N THE HO 260° PEAK TEMPER</li> </ul>	20MM THICK. 5-XXX TIN-LEAD 100 u" THICK . 5-XXXLF PURE TIN 80 u" THICK . ES-14-361, USING TUBE ODUCT MEETS EUROPEN UNION THER COUNTRY REGULATIONS AS -22-008 USING WILL WITHSTAND EXPOSURE TO ATURE FOR 10 SECONDS INA LICATION WITH A 1.60mm MINIMUM
$\begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ &$	$ \frac{1.52}{0} $ $ \frac{0}{9} \xrightarrow{POS}{0} \xrightarrow{6}{0} \xrightarrow{POS}{0} \xrightarrow{6}{0} \xrightarrow{POS}{0} \xrightarrow{7}{0} \xrightarrow{9}{0} \xrightarrow{7}{0} \xrightarrow{7}{0$	8. IF LF P/N PACKAC mat'l. code Surface tolerance pr ISD1302 ISD101 ISD406 ltr ecn nodr date tolerances unless otherwis C T80510 WW 11/18/98 D T03-0443 WL 10/06/03 D T03-0443 WL 10/06/03 E N04-0125 YS 12/15/04 0*±2 0.XXX±0.05 Sc F ULX-N-010215H W0003/25/12/dr C M HSU 03/27/97	CONG MEETS GS-14-920 SPECIFICATION

POS. NO. CONFIGURATION

В

А

А

PDS: Rev :F 3

STATUS:Released

Printed: Sep 1242013

В

form: A4mmXLc

1

2

sheet revisionF index sheet 1