



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





SERIES 628

ADAPTERS / CABLE ASSEMBLIES

ORDERING GUIDE

628 - 000 - 924

SERIES

EDAC INTERNAL

PRODUCT TYPE

SERIES

628 Series

PRODUCT TYPE

- 921 DVI / HD 15 cable assembly
- 922 LFH60 / HD 15 cable assembly
- 923 LFH60 / DVI cable assembly
- 924 DVI / HD 15 adapter
- 924S DVI / HD15 adapter - short black
- 924W DVI / HD15 adapter - short white
- 932 USB A / USB B cable assembly
- 935 RJ11 cable assembly
- 936 RJ45 cable assembly
- 937 SMB / SMB cable assembly
- 940 USB A / mini USB B cable assembly
- 944 USB B / USB B cable assembly
- 945 BNC / SMB cable assembly
- 953 Serial internal cable assembly
- 954 Multiple video cable assembly
- 955 LFH60 / 6XBNC cable assembly
- 957 LFH60 / 4XSCART cable assembly

*For a more complete listing of products, please contact edac@edac.net

FEATURES

- DVI - analog to 15 pin VGA adapter
- High cycle, dual beam low insertion force contacts
- D- subminiature adapting end is polarized
- Fully shielded to protect against EMI / RFI
- 4-40 threaded insert with thumbscrew
- Available in both long and short versions

SPECIFICATIONS

- Insulator material: UL94V-0 thermoplastic polyester
- Shell material: Nickel or tin plated steel
- Current rating: 1.5 amperes
- Dielectric withstanding voltage: 500V for 10 milliseconds
- Insulator resistance: 1000 Megohms at 100V DC
- Voltage: 40 V
- Impedance: 75 Ohms +/- 10% on co-axial wires